HANECO LIGHTING LED INSTALLATION GUIDE

FLEXION 25W 40W IP65 SERIES

Kit Includes:

x1 5m LED strip



x10 Strip Saddles

Important Notes

- Isolate from the mains supply before installation or maintenance.
- The LED strip may be cut to length with cut points every 167mm.
- Flex strips can be connected up to a maximum length of 10m (8mm width).
- **24VDC constant voltage drivers must be used.**
- Ensure that all electrical connections are tight with no loose strands, including factory connections.
- Suitable for mounting on normally flammable surfaces.
- **If longer than 10m length is required, contact Haneco.**

To Install 5m Length

1. Ensure that surface is clean and dry by using an isopropol alcohol

2. Peel off backing tape and fix into position



3. Fasten driver to surface with screws



4. Connect strip to driver

To Shorten Strip Length



1. Strip can be cut at the indicated intervals



2. Cut strip using wire stripper, making sure not to damage contact points

To Extend Strip Length



1. Connect strip to driver



2. Connect end of supply connection plug on one strip to the other end supply connection plug

To Join Intermittent Lengths



1. Expose terminals by removing silicone with knife. Be careful not to damage points



2. Solder supply connection plug, observing polarity

3. Connect end of supply connection plug on one strip to the other

HANECO LIGHTING

For more information
www.haneco.com.au

Lighting Council AUSTRALIA MEMBER