

HANECO
IDEAS THAT SHINE



Rugged Outdoor LED Batten Range

Colour switchable TRIPROOF for tough situations

With a choice of 3 colour temperatures, plus an array of optional smart features, TRIPROOF can go anywhere.

Six-in-one Batten

TRIPROOF models offer double the choice of intensity with Ecoswitch – 20W or 40W. Triple that with Tritone switchable colour temperature and you have versatile 6 in 1 fittings.

Smart Features

Intellisensor models allow you to fine tune the fixtures so that power isn't wasted fully lighting areas that get plenty of natural light or are unoccupied. Emergency versions contain a self-charging Ni-Cd battery that keeps the light on low for 3 hours during a blackout.

Energy Efficient

All of Haneco's LED battens deliver markedly better energy efficiency than fluorescents and have at least five times the lifespan. Government energy saving schemes confirm this with accreditation for several models in **VEET**, **REES** and **IPART**.

Long list of applications

TRIPROOF can find a place in sports halls, commercial kitchens (HACCP approved), schools, car parks, indoor and outdoor stairwells, public amenities and a range of industrial spaces.

Environmentally Friendly

None of our battens contain mercury or other toxic material.

**Colour
Switchable
Tritone**



info@haneco.com.au | Ph: **1300 001 LED**

haneco.com.au

Dust ✓
Moisture ✓
Impact ✓
Proof

Smart and Durable LED Battens

Tritone TRIPROOF offers smart options in several combinations

- Tritone selection of 3 colour temperatures available on all but 1-10V Dimming model
- IK08 vandal resistant rated and weatherproof IP65
- Approved for use in food preparation areas by HACCP
- **Ecoswitch** allows you to switch to half power
- **Intellisensor** is a programmable occupancy sensor that dims the light when no-one is around
- **Sunmax** daylight harvesting can be used with 1-10V Dimming model with one sensor controlling up to 25 TRIPROOF units in a zone

SIZE	KEY FEATURES	CCT	WATT	LUMEN	PRODUCT CODE
618mm		4000K 5000K 6500K	20W	1850lm 1990lm 1850lm	TRIPROOF20W06-TRI
618mm	Emergency	4000K 5000K 6500K	20W	1850lm 1990lm 1850lm	TRIPROOF20W06-TRI-EM
1215mm	Ecoswitch VEET IPART REES	4000K 5000K 6500K	20W-40W	2227lm-4090lm 2254lm-4410lm 1965lm-4050lm	TRIPROOF20/40W12-TRI
1215mm	Ecoswitch Emergency VEET IPART REES	4000K 5000K 6500K	20W-40W	2227lm-4090lm 2254lm-4410lm 1965lm-4050lm	TRIPROOF20/40W12-TRI-EM
1215mm	Intellisensor VEET IPART REES	4000K 5000K 6500K	40W	4510lm 3830lm 3350lm	TRIPROOF40W12-TRI-SS
1215mm	Intellisensor Emergency	4000K 5000K 6500K	40W	4090lm 4410lm 4050lm	TRIPROOF40W12-TRI-SS-EM
1215mm	1-10V Dim	5000K	40W	3610lm	TRIPROOF40W12-5K-10VDIM
1515mm		4000K 5000K 6500K	60W	5600lm 6000lm 5700lm	TRIPROOF60W15-TRI