



# ARIS150W

ARIS150W40x120

SAP CODE: 2002032



Photometric Diagram



Unit: cd  
C0/180 36.0deg  
C90/270 111.1deg

## 150W 40x120D LED Linear Highbay

ARIS is a series of waterproof smooth line linear highbays complete with asymmetric lens and 0-10V dimmable integral driver.

### KEY INFORMATION

Lumen Output	18580lm
Input Power	150W
Hole Cutout Size	N/A
Install	SURFACE MOUNT
Dimming Options	0-10V Dimming
Fitting Colour	BLACK
Warranty	5yr
IP Rating	IP65
IK Rating	IK10
IC Rating	N/A
Rebate Scheme Approvals	Pending Approval

### PHOTOMETRIC

Efficacy	125lm/W
LED	SMD
CCT	5000K
CRI	>80
Beam Angle	40x120

### ELECTRICAL

Driver	Integral
Supply Input	220-240V, 50/60Hz
Driver Output Voltage	200V DC
Power Factor	>0.9
LED Input Current (nominal)	750mA
Useful life @Ta25° (L70)	50,000hr

### CONSTRUCTION

Housing	Aluminium
Optics	PMMA (acrylic)
Adjustable Angle	0-180°
Fixings/Hardware	Mounting Bracket
Connection Type	1.2m Flex & Plug
Total Weight	3.5kg
Dimensions	845 x 124 x 141mm
Operating Ambient Temp.	-20 to 50°C
Electrical Classification	Class 1