

ASTRAL

AST10W-115-WW SAP CODE: 2002609


Premium, low glare.

The ASTRAL LED Light range meets market demands with a complete selection of sizes and optional reflectors to suit every designer's needs. Each variant complies with Greenstar requirements, ensuring high performance for commercial applications. With high lumen outputs, a tight beam angle, tritone, and dimming technology, ASTRAL is the go-to solution for commercial lighting.

APPLICATIONS


Bathrooms, Boardroom / Meeting Rooms, Cocktail Lounges, Medical Facilities, Hotel Common Areas, Hotel Rooms, Offices, Retail Spaces, Showrooms, Entrances, Food Courts, Restaurants / Cafes

DIMENSION DIAGRAMS





PHOTOMETRIC DIAGRAM



Unit: cd

- C0/180 63.0deg
- C90/270 61.6deg

Photometric diagram shown is for

KEY INFORMATION		
Power	10 W	
Lumen Output	954 / 1020 lm	
Cutout Size	Ø 90 mm	
Mounting Type	Recessed	
Dimming Type	Phase-Cut Dimmable (Trailing Edge, 10-100%)	
Body Colour	White	
IP Rating	IP54 F - IP20 B	
IC Rating	IC-4 (Lamp Only)	
Operating Ambient Temp.	-20°C to 45°C	
Connection Type	0.6m Flex & Plug	
Driver	Remote	
Warranty	5 yrs	

PHOTOMETRIC	
Efficacy	88 / 97 lm/W
ССТ	3000 / 4000 K
CRI	> 90
SDCM	<3
UGR	< 19
Beam Angle	60°
Flicker-Free	Yes
Projected Lifespan	54,000hrs @ Ta25°C(L80)

ELECTRICAL	
Input Voltage	220-240VAC
Driver Output Voltage	30-40V DC
Driver Output Current	230 mA
Power Factor	> 0.9
Electrical Classification	Class II
Surge Protection	Overload / Short Circuit

OTHERS		
Adjustable Angle	Not Applicable	
Body Material	Aluminium	
Diffuser Material	РММА	
Rebate Scheme Approvals	Not Applicable	
HACCP Approval	No	
Weight	0.2 kg	
Dimensions	Ø115 x 65 mm	
		