



# ASTRO

## Commercial Downlights

**CLASS 2**  
Double Insulated

**TRITONE**  
Colour Changeable

**2POWER**  
Switchable Modes

**IP54**  
Ingress Protection Rating

**UGR<19**  
Beam Angle

**50,000hr**  
Expected Lifetime

**5yr**  
Warranty

### Premium, low glare.

The superior ASTRO range removes glare and adds visual comfort due to its deep recessed diffuser and specular reflector system, providing maximum lighting output and optimal performance. This high-performance downlight is the ideal choice for high-end interior spaces.

### Features

- Tritone and power switchable
- Flicker-free driver
- UGR <19
- IP54 (from below)
- Complete with flex and plug
- Surface mount and trim accessories

### Benefits

- Reduced SKUs and inventory levels
- Increased health and productivity
- Reduced glare and visual comfort
- Perfect for wet areas
- Quick and easy installation
- Extended application possibilities

POWER	LUMENS	EFFICACY	CCT	CUTOUT	WEIGHT	SAP CODE	PRODUCT CODE
15W	1400 lm	93 lm/W	3000K	Ø170mm	0.66kg	2001946	<b>ASTRO25W195R</b>
	1550 lm	103 lm/W	4000K				
	1500 lm	100 lm/W	5700K				
25W	2200 lm	88 lm/W	3000K				
	2400 lm	96 lm/W	4000K				
	2300 lm	92 lm/W	5700K				
24W	2100 lm	86 lm/W	3000K	Ø210mm	0.83kg	2001947	<b>ASTRO30W230R</b>
	2300 lm	96 lm/W	4000K				
	2200 lm	92 lm/W	5700K				
32W	2850 lm	89 lm/W	3000K	-	1.90kg	2002008	<b>ASTRO30W-SM</b>
	3100 lm	97 lm/W	4000K				
	3000 lm	94 lm/W	5700K				

R = Recessed SM = Surface Mount

### SPECIFICATIONS

<b>Body Material:</b>	Aluminium
<b>Diffuser Material:</b>	Polycarbonate (Clear)
<b>Reflector:</b>	Chrome
<b>Fascia Colour:</b>	White: RAL9016
<b>IP Rating:</b>	Front: IP54 Body: IP20
<b>Beam Angle:</b>	55°
<b>CRI:</b>	>80 (>90 option)
<b>UGR:</b>	<19
<b>SDCM:</b>	<5 (<3 option)

<b>Driver:</b>	Remote
<b>Power Lead:</b>	1m Flex & Plug
<b>Link Lead:</b>	550mm Cable with JST Connector
<b>Input:</b>	220-240V, 50/60Hz
<b>Electrical Classification:</b>	Class 2
<b>Power Factor:</b>	>0.9
<b>Protection:</b>	Overload / Short Circuit
<b>Lifespan:</b>	>50,000hrs @Ta25°C (L70)
<b>Operating Ambient Temperature:</b>	-20 to 40°C
<b>Smart:</b>	KASTA Compatible
<b>Dimming:</b>	Non-Dimmable

Phase-Cut, 0/1-10V and DALI Dimmable Models Available. See Page 212.

### APPLICATIONS

Retail  
Hospitality  
Function Areas  
Office

### ACCESSORIES

#### ASTRO30W230R:

**Adaptor Ring Ø280mm**  
(Cut Out Ø230-260mm)  
**TRIM-C2030-280-W**  
(SAP 2001219)









**Adaptor Ring Ø310mm**  
(Cut Out Ø230-280mm)  
**TRIM-310-W**  
(SAP 2002222)



ASTRO30W-SM

### DIMENSIONS



Remote Driver: 127 x 43 x 28mm

Remote Driver: 127 x 43 x 28mm

ASTRO25W195R

ASTRO30W230R

ASTRO30W-SM

FIND OUT MORE:

