



# AURORA

## AURORA-WH-TRI

SAP CODE: 2002336



### All features in a slimline package.

AURORA is the premium luminaire for residential spaces. Equipped with a cutting-edge RippleGuard driver, AURORA filters out specific frequencies (750-1050Hz) used by energy providers in QLD and NSW. It also features Tritone for color selection and a remote flicker-free dimmable driver for visual comfort. The compact height allows for fast and efficient installation in tight spaces, making it suitable for various applications. A DALI dimmable driver is available as an option.


#### APPLICATIONS

Lounge Room, Dining Area, Hallways, Entrance, Staircase, Bathrooms, Walk-in Wardrobes, Theatre Rooms, Balconies / Patios / Verandahs, Awnings, Showrooms, Offices, Function Areas, Hotel Rooms, Kitchen / Food Prep

#### DIMENSION DIAGRAMS



#### PHOTOMETRIC DIAGRAM



Unit: cd  
 - C0/180 100.0deg  
 - C90/270 100.0deg

Photometric diagram shown is for 4200K output.

#### KEY INFORMATION

Power	10 W
Lumen Output	950 / 1100 / 1000 lm
Cutout Size	90 mm
Mounting Type	Recessed
Dimming Type	Phase-Cut Dimmable (Trailing Edge, 1-100%)
Body Colour	White
IP Rating	IP44 F - IP20 B
IC Rating	IC-4
Operating Ambient Temp.	-25 to 45°C
Connection Type	1m Flex & Plug
Driver	Remote
RippleGuard Driver	Yes
Warranty	5 yrs

#### PHOTOMETRIC

Efficacy	90 / 100 / 95 lm/W
CCT	3000 / 4200 / 5700 K
CRI	> 80
SDCM	< 5
UGR	< 31
Beam Angle	100°
Flicker-Free	Yes
Projected Lifespan	>72,000hrs@Ta25°C(L70)

#### ELECTRICAL

Input Voltage	220-240Vac 50/60Hz
Driver Output Voltage	15-30V DC
Driver Output Current	300mA
Power Factor	> 0.9
Electrical Classification	Class II
Surge Protection	Overload / Short Circuit

#### OTHERS

Adjustable Angle	Not applicable
Body Material	Aluminium
Diffuser Material	Polycarbonate (Opal)
Rebate Scheme Approvals	Not Applicable
Weight	0.3 kg
Dimensions	Ø110 x 37.5 mm