



AURORA 80

AURORA80-WH

SAP CODE: 2002342


Compact and versatile.

Experience the elegance and versatility of the AURORA 80, a compact yet powerful downlight designed to illuminate even the most challenging spaces. With its sleek design and advanced features, the AURORA 80 offers the same sophisticated appeal as its larger counterpart, the AURORA, in a more compact form.

APPLICATIONS

Bedrooms, Accent / Display / Feature Lighting, Walk-in Wardrobes, Theatre Rooms, Games Rooms, Hotel Rooms

DIMENSION DIAGRAMS




Disclaimer

NOTE1: SDCM Value measured at 3K CCT.



PHOTOMETRIC DIAGRAM



Unit: cd

— C0/180, 92.8

— C90/270, 93.0

Photometric diagram shown is for 4000 K output.

KEY INFORMATION

Power	7 W
Lumen Output	665 / 708 / 669 lm
Cutout Size	70 mm
Mounting Type	Recessed
Dimming Type	Phase-Cut Dimmable (Trailing Edge, 10-100%)
Body Colour	White
IP Rating	IP54 F - IP20 B
IC Rating	IC-4
Operating Ambient Temp.	-25 to 45°C
Connection Type	0.9m Flex & Plug
Driver	Remote
Warranty	5 yrs

PHOTOMETRIC

Efficacy	95 / 101 / 95 lm/W
CCT	3000 / 4000 / 5700 K
CRI	> 85
SDCM	< 3
UGR	> 25
Beam Angle	95°
Flicker-Free	Yes
Projected Lifespan	>80,000hrs @Ta25°C (L80)

ELECTRICAL

Input Voltage	220-240Vac 50/60Hz
Driver Output Voltage	Not applicable
Driver Output Current	180 mA
Power Factor	> 0.9
Electrical Classification	Class II
Surge Protection	Overload / Short Circuit

OTHERS

Adjustable Angle	Not applicable
Body Material	Aluminium
Diffuser Material	Polycarbonate (Opal)
Rebate Scheme Approvals	Not Applicable
HACCP Approval	No
Weight	0.2 kg
Dimensions	Ø85 x 39 mm