

BATTEN-REMOTE

Thanks for choosing our **BATTEN-REMOTE** products.

We strongly recommend that you read this manual carefully before installation.

Compatible Product Code:TRIPROOF12-MS, TRIPROOF12-MS-EM

VISTA-EV12-MS, VISTA-EV12-EM-MS, VISTA-EV12-MS-BK, VISTA-EV12-EM-MS-BK

DURA-SENKIT-G2, MULTI-P-MS

The IR-based handheld remote control allows convenient reconfiguration of all Haneco sensors with integrated IR module. ONE IR remote control can reprogram multiple RC sensor switches.

Remote Control Setting	Button	Remarks																												
		Press the "ON/OFF" button, the light goes to constant on/off mode, sensor is disabled. Press "Reset" "Auto mode" button to quit from this mode and the sensor starts to work. No memory for ON-OFF setting after power off. Sensor mode will auto recover after restart power supply.																												
	Reset	Press "Reset" button, all parameters are same as setting of DIP switch or factory settings.																												
		Press "Sensor motion" button, the light quits from the constant on/ off mode, and the sensor starts to work (The latest setting stays in validity)																												
		Press "DIM Test" button, the 1-10 V dimming works to test whether the 1-10Vdc dimming ports are connected properly. After 2s, it returns to the latest setting automatically.																												
	Override DH	NOT APPLICABLE																												
	DIM+ DIM-	Short press "Dim+/Dim-" button to Set the output lumen level, each press will ±2% light level.																												
		NOT APPLICABLE																												
	Q1 Q2 Q3	<table><tr><th>Scene Options</th><th>Detection Area</th><th>Hold Time</th><th>Stand-by period</th><th>Stand-by dim level</th><th>Daylight Sensor</th><th>Induction model</th></tr><tr><td>QS1</td><td>100%</td><td>5min</td><td>10min</td><td>10%</td><td>30Lux</td><td>HS</td></tr><tr><td>QS2</td><td>100%</td><td>10min</td><td>30min</td><td>10%</td><td>Disable</td><td>HS</td></tr><tr><td>QS3</td><td>100%</td><td>20min</td><td>30min</td><td>10%</td><td>Disable</td><td>HS</td></tr></table>	Scene Options	Detection Area	Hold Time	Stand-by period	Stand-by dim level	Daylight Sensor	Induction model	QS1	100%	5min	10min	10%	30Lux	HS	QS2	100%	10min	30min	10%	Disable	HS	QS3	100%	20min	30min	10%	Disable	HS
	Scene Options	Detection Area	Hold Time	Stand-by period	Stand-by dim level	Daylight Sensor	Induction model																							
	QS1	100%	5min	10min	10%	30Lux	HS																							
	QS2	100%	10min	30min	10%	Disable	HS																							
	QS3	100%	20min	30min	10%	Disable	HS																							
	TEST 2S	Note: Detection area / Hold time / Stand-by period / Stand-by dim level / Daylight sensor can be adjusted by pressing the corresponding button. The latest setting will stay valid. Press the "TEST 2S" button can enter the test mode any time. At the mode, the sensor parameters as below: Detection Area is 100%, Hold Time is 5s, Stand-by Dim Level is 10%, Stand-by Period is 0s, daylight sensor disable. This function only for testing. Quit the mode by pressing "RESET" or any other function buttons.																												
	HS LS	Press "HS" button to set the detection area to be high sensitive. Press "LS" button to set the detection area to be low sensitive. The adjustment bases on the "Detection Area" parameter you set.																												
		Daylight Sensor Set up daylight threshold: 5Lux/15Lux/30Lux/50Lux/100Lux/150Lux/ Disable																												
		Stand-by period Set up stand-by time: 0S/10S/1min/3min/5min/10min/30min/+∞																												
		Hold time Set up hold time: 5S/30S/1min/3min/5min/10min/20min/30min																												
	Stand-by dim level Set up stand-by dim level: 10%/20%/30%/50%																													
	Detection Area Set up detection area: 25%/50%/75%/100%																													
	Remote Distance Toggle button can set the remote distance of remote control and sensor.																													

Technical specifications:

- Suitable for all Haneco sensors with integrated IR reception.
- Operating voltage: 3V via 2 x AAA batteries (not included)
- Range approx. 20 m (depending on local conditions and battery level).
- Dimensions: 175 x 55 x 22 mm

Product Code: **BATTEN-REMOTE**