



CEDAR

Commercial Downlights


CLASS 2
Double Insulated


IP40
Ingress Protection Rating


0-90°
Adjustment Angle


50,000hr
Expected Lifetime


5yr
Warranty

Recessed adjustable design.

CEDAR available in round or square, is a powerful and economical, adjustable shoplight with multifaceted reflector technology and frosted lens for ideal glare control.

Features

- Available in round or rectangle design
- 0-90° adjustable tilt
- Multifaceted reflector system (round model)
- Frosted lens
- Complete with flex and plug

Benefits

- Suitable for a wide range of applications
- Full flexibility in terms of shop layout
- Enhanced glare control
- Increased visual comfort
- Quick and easy installation

Product Overview

DESIGN	POWER	LUMENS	EFFICACY	CCT	CUTOUT	WEIGHT	SAP CODE	PRODUCT CODE
Round	38W	3050 lm	80 lm/W	4000K	Ø165mm	1.50kg	2000151	D38W195R4K60DF
Rectangular	40W	4160 lm	104 lm/W	4000K	220 x 130mm	1.50kg	2000534	D40W242*150RE4K90DF
		4100 lm	103 lm/W	5000K			2000536	D40W242*150RE5K90DF

SPECIFICATIONS

Body Material:	Aluminium	Driver:	Remote
Diffuser Material:	Polycarbonate (Frosted)	Power Lead:	1.1m Flex & Plug
Reflector:	Multifaceted	Link Lead:	150/180mm Cable with Flat JST Connector
Fascia colour:	White: RAL 9003 (38W) White: RAL 9010 (40W)	Input:	220-240V, 50/60Hz
IP Rating:	Front: IP40 (38W) Front: IP40 (40W) Body: IP20 (38W) Body: IP40 (40W)	Electrical Classification	Class 2
Beam Angle:	70°	Power Factor:	>0.9
Gimbal:	0-90°	Protection:	Overload / Short Circuit
CRI:	>80 (>90 option)	Lifespan:	>50,000hrs @Ta25°C (L70)
SDCM:	<5 (<3 option)	Operating Ambient Temperature:	-20 to 50°C
		Smart:	KASTA Compatible
		Dimming:	Non-Dimmable DALI Dimmable Models Available. See Page 212.

APPLICATIONS

Retail
Hospitality
Commercial
Lobbies

Commercial Downlights





Round





Rectangular

DIMENSIONS



Remote Driver: 91 x 38 x 28mm

D38W195R4K60DF



Remote Driver: 156 x 50 x 33mm

D40W242*150RE4K90DF
D40W242*150RE5K90DF

FIND OUT MORE:

