


# CEDAR

D40W242\*150RE4K90DF

SAP CODE: 2000534




40W, 4000K, diffused, adjustable LED shoplight

Powerful rectangular shoplight in a traditional design that can be adjusted.



Photometric Diagram



Unit: cd  
 - C0/180 85.0deg  
 - C90/270 85.0deg

## KEY INFORMATION

Lumen Output	4160lm
Input Power	40W
Hole Cutout Size	130x220mm
Install	RECESSED
Dimming Options	Non-Dimmable
Trim Colour	WHITE
Warranty	5yr
IP Rating	IP40
IK Rating	N/A
IC Rating	NON-IC
Rebate Scheme Approvals	VEET; REES; IPART LCP 43.49

## PHOTOMETRIC

Efficacy	104lm/W
LED	SMD
CCT	4000K
CRI	>80
Beam Angle	70°

## ELECTRICAL

Driver	Remote
Supply Input	220-240V, 50/60Hz
Driver Output Voltage	36VDC
Power Factor	>0.9
LED Input Current (nominal)	1050mA
Useful life @Ta25° (L70)	50,000hr

## CONSTRUCTION

Housing	Aluminium
Optics	Polycarbonate Diffuser
Adjustable Angle	0-70°
Fixings/Hardware	Rubberised Clip
Connection Type	1.1m Flex & Plug
Total Weight	1.5kg
Dimensions	242x150x105mm
Operating Ambient Temp.	-20 to 50°C
Electrical Classification	Class 2