

DIONEResidential Downlights











Powerful and directional.

DIONE is a high output, adjustable IP54 rated LED downlight with wide faceted reflector to ensure uniform light distribution for even wall washing.

Features

- Wide faceted reflector
- Slim trim design
- Adjustable LED downlight
- IP54 ingress protection
- Complete with flex and plug

Benefits

- Uniform and even wall washing
- · Appears flush and neat in the ceiling
- Increased flexibility
- Ideal for wet areas
- Quick and easy installation

DIONE

Product Overview



POWER	LUMENS	EFFICACY	сст	ситоит	WEIGHT	FASCIA	SAP CODE	PRODUCT CODE	
45147	1100 l	00 les /M	200014	Ø85mm	0.9kg	White	2000145	D15W109R3KW	
15W	1190 lm	80 lm/W	3000K	Wesillili		Silver	2000144	D15W109R3KS	Ī

SPECIFICATION	PECIFICATIONS					
Body Material:	Aluminium					
Diffuser Material:	Polycarbonate (Clear)					
Fascia colour:	White: RAL9010 Silver: RAL7001					
IP Rating:	Front: IP54 Body: IP40					
Beam Angle:	45°					
Gimbal:	0-30°					
CRI:	>80 (>90 option)					
SDCM:	<5 (<3 option)					

Driver:	Remote
Power Lead:	1.1m Flex & Plug
Input:	220-240V, 50/60Hz
Electrical Classification:	Class 2
Power Factor:	>0.9
Protection:	Overload / Short Circuit
Lifespan:	>50,000hrs @Ta25°C (L70)
Operating Ambient Temperature:	-20 to 50°C
Smart:	KASTA Compatible
Dimming:	Phase-Cut Dimmable (Trailing Edge)

APPLICATIONS					

ACCESSORIES

Surface Mount Kit: SM-ENC-DL (SAP 2001870)



Suspension Kit: SM-ENC-SUSKIT (SAP 2001871)










Silver



DIMENSIONS



Remote Driver 120x45x27mm

D15W109R3K



