


# DISCUS

DISC25W300R

SAP CODE: 2001935




## 25W, Ultra-slim, Weather Resistant, Tritone LED Oyster

A sleek, aesthetically designed oyster with a slim body profile for both indoor and outdoor applications.



Photometric Diagram



Unit: cd  
 - C0/180 114.5deg  
 - C90/270 114.1deg

### KEY INFORMATION

Lumen Output	2040 / 2190 / 2080lm
Input Power	25W
Hole Cutout Size	N/A
Install	SURFACE MOUNT
Dimming Options	*Phase-Cut Dimming
Fitting Colour	WHITE
Warranty	5yr
IP Rating	IP54
IK Rating	IK08
IC Rating	N/A
Rebate Scheme Approvals	Pending Approval

### PHOTOMETRIC

Efficacy	81 / 87 / 83lm/W
LED	SMD
CCT	3000 / 4000 / 5700K
CRI	>80
Beam Angle	115°

### ELECTRICAL

Driver	Integral
Supply Input	220-240V, 50/60Hz
Driver Output Voltage	60V DC
Power Factor	>0.9
LED Input Current (nominal)	400mA
Useful life @Ta25° (L70)	50,000hr

### CONSTRUCTION

Housing	Polycarbonate
Optics	PMMA (acrylic)
Adjustable Angle	N/A
Fixings/Hardware	Mounting Bracket
Connection Type	Terminal Block
Total Weight	0.75kg
Dimensions	Ø300 x 38mm
Operating Ambient Temp.	-20 to 45°C
Electrical Classification	Class 2

\*Dimming performance may vary depending on the specifications of the dimmer being used. For best performance use Haneco or KASTA dimmers.