



DULAR^{FIX} G2

Residential Downlights

For comfortable, low glare environments.

DULAR is a deep-recessed LED downlight designed to deliver exceptional visual comfort. Featuring an ultra-slim trim and advanced low-glare optical design, DULAR achieves UGR<19 and CRI90 excellent lighting. The new engineered lens not only enhances visual comfort but also adds a clean, sophisticated appearance to the fitting, ensuring a perfect balance of performance and design for high-end lighting project

Features

- Tritone colour changeable
- High Colour Rendering Index (CRI)
- IC-4 rating (ta 25 °C)
- Exceptional performance
- Low Unified Glare Rating (UGR)
- Dimmable driver
- Flicker-free driver

Benefits

- Provides the choice of light hues from a single luminaire
- True colour definition to highlight natural colour
- Allows for covered and abutted installations
- High efficiency rating to promote energy saving
- Excellent lighting option for indoor work places
- Adjustable brightness to improve comfort
- Increase productivity and lowers eye strain



POWER	LUMENS	EFFICACY	CCT	CUTOUT	WEIGHT	FASCIA	SAP CODE	PRODUCT CODE
7 W	800 / 900 / 850 lm	114 / 129 / 121 lm/W	3000 / 4000 / 5700 K	Ø 90 mm	0.25 kg	White	2002701	DULAR-G2
7 W	800 / 900 / 850 lm	114 / 129 / 121 lm/W	3000 / 4000 / 5700 K	Ø 90 mm	0.25 kg	Black	2002702	DULAR-BLK-G2

SPECIFICATIONS			
Body Material:	Polyamide	Driver:	Remote
Diffuser Material:	Polycarbonate Lens	Connect Type:	0.9m Flex & Plug
Body Colour:	White / Black	Electrical Classification:	Class II
IP Rating:	IP44 (front only)	*Projected Lifespan:	102,000hrs @ Ta25°C(L70)
IC Rating:	IC-4	Operating Ambient Temp.	-20 to 40°C
Flick-free Driver:	Yes	Power Factor:	> 0.9
Beam Angle:	45°	Surge Protection:	Overload / Short Circuit
CRI	> 90	UGR	< 19
SDCM:	< 3	Smart:	KASTA Compatible
Dimming:	Phase-Cut Dimmable (Trailing Edge, 10-100%)		

APPLICATIONS	
Bathrooms	Offices
Boardroom / Meeting Rooms	Retail Spaces
Cocktail Lounge	Showrooms
Medical Facilities	Restaurants / Cafes
Hotel Common Areas	Entrance
Hotel Rooms	Food Courts

*Based on rated LED design life

DIMENSIONS (mm)

