

DULAR

DULAR-ADJ-TRI 2002334

FOR COMFORTABLE, LOW GLARE ENVIROMENTS

Learn about the DULAR from HANECO, the ideal home LED downlight that comes in fixed and adjustable beam angle variants with an assortment of facia colours for both varieties. The DULAR is a beautiful option designed for applications that are attractive to the eye.

APPLICATIONS

Bedroom

Lounge Room

Dining Area

Kitchen / Food Prep

Laundry

Butler Pantry

Hallway

Entrance Accent / Display / Feature

Lighting

Staircase

Bathroom

Ensuite

Walk-In Wardrobe

Theatre Room

Games Room

Showroom

Boardroom / Meeting Rooms

Function Areas

Education Facilities


Retail Spaces

Hotel Rooms

Restaurants / Café's

Cocktail Lounge





Unit: cd - C0/180 45.0deg - C90/270 45.0deg

KEY INFORMATION	
Power	7 W
Lumen Output	800 / 900 / 850 lm
Cutout Size	90 mm
Mounting Type	Recessed
Dimming Type	Phase-Cut Dimmable (Trailing Edge, 10-100%)
Body Colour	White
IP Rating	IP44 Front - IP20 Back
IC Rating	IC
Rebate Scheme Approvals	Not Applicable
Driver	Integral
Warranty	5 Years

PHOTOMETRIC	
Efficacy	114 / 129 / 121 lm/W
ССТ	3000 / 4000 / 5700 K
CRI	> 90
SDCM	< 3
UGR	< 21
Beam Angle	45°
Flicker-Free	Yes
Lifespan	>50,000hrs

ELECTRICAL	
Input Voltage	220-240Vac, 50/60Hz
Power Factor	> 0.9
Electrical Classification	CLASS II
Surge Protection	Overload / Short Circuit

OTHERS	
Angle Flexibility	0 - 30°
Body Material	Aluminium / Polycarbonate
Diffuser Material	Polycarbonate (Multifaceted)
Operating Ambient Temp.	⁻ 20 to 45°C
Connection Type	1m Flex & Plug
Weight	0.29 kg
Dimensions	Ø110 mm x 74 mm