

DULAR


DULAR-ADJ-TRI
2002334

FOR COMFORTABLE, LOW GLARE ENVIROMENTS

Learn about the DULAR from HANECO, the ideal home LED downlight that comes in fixed and adjustable beam angle variants with an assortment of fascia colours for both varieties. The DULAR is a beautiful option designed for applications that are attractive to the eye.

APPLICATIONS

Bedroom
 Lounge Room
 Dining Area
 Kitchen / Food Prep
 Laundry
 Butler Pantry
 Hallway
 Entrance Accent / Display / Feature Lighting
 Staircase
 Bathroom
 Ensuite
 Walk-In Wardrobe
 Theatre Room
 Games Room
 Showroom
 Boardroom / Meeting Rooms
 Function Areas
 Education Facilities
 Retail Spaces
 Hotel Rooms
 Restaurants / Cafés
 Cocktail Lounge



Unit: cd
 - C0/180 45.0deg
 - C90/270 45.0deg

KEY INFORMATION

Power	7 W
Lumen Output	800 / 900 / 850 lm
Cutout Size	90 mm
Mounting Type	Recessed
Dimming Type	Phase-Cut Dimmable (Trailing Edge, 10-100%)
Body Colour	White
IP Rating	IP44 Front - IP20 Back
IC Rating	IC-4
Rebate Scheme Approvals	Not Applicable
Driver	Integral
Warranty	5 Years

PHOTOMETRIC

Efficacy	114 / 129 / 121 lm/W
CCT	3000 / 4000 / 5700 K
CRI	> 90
SDCM	< 3
UGR	< 21
Beam Angle	45°
Flicker-Free	Yes
Lifespan	>100,000hrs@Ta45°C(L70)

ELECTRICAL

Input Voltage	220-240Vac, 50/60Hz
Power Factor	> 0.9
Electrical Classification	CLASS II
Surge Protection	Overload / Short Circuit

OTHERS

Angle Flexibility	0 - 30°
Body Material	Aluminium / Polycarbonate
Diffuser Material	Polycarbonate (Multifaceted)
Operating Ambient Temp.	-20 to 45°C
Connection Type	1m Flex & Plug
Weight	0.29 kg
Dimensions	Ø110 mm x 74 mm