


DULAR

DULAR-FIX-BLK 2002333





Unit: cd -- C0/180 45.0deg -- C90/270 45.0deg

## **KEY INFORMATION** 7 W Power Lumen Output 750 / 850 / 800 lm Cutout Size 90 mm Recessed Mounting Type Phase-Cut Dimmable (Trailing Edge, 10-100%) **Dimming Type Body Colour** Black **IP** Rating IP44 Front - IP20 Back IC-4 **IC Rating** Rebate Scheme Not Applicable Approvals Driver Integral 5 Years Warranty PHOTOMETRIC Efficacy 107 / 121 / 114 lm/W ССТ 3000 / 4000 / 5700 K CRI > 90 < 3 SDCM < 19 UGR **Beam Angle** 45° Flicker-Free Yes Lifespan >100,000hrs@Ta45°C(L70) ELECTRICAL 220-240Vac, 50/60Hz Input Voltage **Power Factor** > 0.9 CLASS II **Electrical Classification** Overload / Short Circuit Surge Protection OTHERS Angle Flexibility Not Applicable Aluminium / Polycarbonate **Body Material** Diffuser Material Polycarbonate (Multifaceted) **Operating Ambient** -20 to 45°C Temp. Connection Type 1m Flex & Plug Weight 0.25 kg Ø98 mm x 79 mm Dimensions

## FOR COMFORTABLE, LOW GLARE ENVIROMENTS

Learn about the DULAR from HANECO, the ideal home LED downlight that comes in fixed and adjustable beam angle variants with an assortment of facia colours for both varieties. The DULAR is a beautiful option designed for applications that are attractive to the eye.

## APPLICATIONS

Bedroom Lounge Room **Dining Area** Kitchen / Food Prep Laundry **Butler Pantry** Hallway Entrance Accent / Display / Feature Lighting Staircase Bathroom Ensuite Walk-In Wardrobe **Theatre Room** Games Room Showroom Boardroom / Meeting Rooms **Function Areas Education Facilities Retail Spaces** Hotel Rooms Restaurants / Café's Cocktail Lounge

🔎 haneco.com.au