



DURA FOREMAN

DURA-12-FRMN-EM

SAP CODE: 2002544

Temporary weatherproof solution.

Illuminate your construction site with the DURA FOREMAN, an energy-efficient weatherproof batten designed for temporary applications. Perfect for commercial, residential, and infrastructure projects, the DURA FOREMAN offers a safe and flexible lighting solution.


APPLICATIONS

Temporary Installations

DIMENSION DIAGRAMS



PHOTOMETRIC DIAGRAM



Unit: cd

— C0/180, 143.0

— C90/270, 107.7

Photometric diagram shown is for 4000 K output.

KEY INFORMATION

Power	36 W
Lumen Output	Standard Mode: 4094 lm EM Mode: 223 lm
Mounting Type	Surface Mount / Suspended
Dimming Type	Non-Dimmable
Fascia Colour	Grey
IP Rating	IP65
IK Rating	IK08
Operating Ambient Temp.	-0 to 40°C
Connection Type	1.7m Flex & Plug
Driver	Integral
Warranty	1 yr

PHOTOMETRIC

Efficacy	115 lm/W
CCT	4000 K
CRI	> 80
SDCM	< 5
UGR	Not Applicable
Beam Angle	120°
Flicker-Free	Yes
Projected Lifespan	>50,000hrs @ Ta 25°C (L70)

ELECTRICAL

Input Voltage	220-240Vac, 50/60Hz
Power Factor	> 0.9
Electrical Classification	Class I
Surge Protection	Overload / Short Circuit
Power Charging	3 W
Power Standby	0.5 W

EMERGENCY INFORMATION

Test Type	Manual Test
Battery Type	LiFePO4 3.2V 2Ah
Recharge Time	16 hrs
Discharge Time	2 hrs
Emergency Classification	C0: D40 C90: D16