

# DURA G2

## DURA06-EM-G2

SAP CODE: 2002602

### Tougher, smarter, and built to last.


Built for performance and designed with flexibility in mind, the DURA G2 batten is the go-to solution for challenging environments such as car parks, warehouses, workshops, and public facilities.

With IP65 and IK08 ratings, flicker-free light output, and a new modular motion sensor kit (available as an accessory) compatible with both standard and emergency models.

### APPLICATIONS

Carpark, Carport, Storage Facilities, Storage Rooms, Warehouse, Kitchen/Food Prep, Balconies/Patios/Verandas, Awnings, Garage, Shed, Side of Building, Manufacturing Facilities, Hangers, Public Facilities, Temporary Installations, General Industrial

### DIMENSION DIAGRAMS



#### Disclaimer


NOTE1: +3W while Battery charging  
NOTE2\*: Based on rated LED design life

 [haneco.com.au](http://haneco.com.au)

Specification subject to change without prior notice. Last updated 11/08/2025



### PHOTOMETRIC DIAGRAM



Unit: cd  
— C0/180 128.5deg  
— C90/270 108.3deg

### KEY INFORMATION

Power	10 W 13 W 15 W 18 W
Lumen Output	1229 / 1260 / 1189 lm 1591 / 1659 / 1539 lm 1888 / 1986 / 1827 lm 2184 / 2328 / 2107 lm
Mounting Type	Surface Mount / Suspended
Dimming Type	Non-Dimmable
Fascia Colour	Grey
IP Rating	IP65
IK Rating	IK08
Operating Ambient Temp.	0 to 40°C
Connection Type	PA12 Terminals
Driver	Integral
Warranty	5 yrs

### PHOTOMETRIC

Efficacy	10 W: 119 / 126 / 116 lm/W 13 W: 121 / 131 / 118 lm/W 15 W: 119 / 130 / 116 lm/W 18 W: 115 / 129 / 112 lm/W
CCT	4000 / 4500 / 5000 K
CRI	> 80
SDCM	< 5
UGR	< 25
Beam Angle	120°
Flicker-Free	Yes
Projected Lifespan*	>102,000hrs @ Ta 40°C (L70)

### ELECTRICAL

Input Voltage	220-240Vac, 50/60Hz
Power Factor	> 0.9
Electrical Classification	Class I
Surge Protection	Overload / Short Circuit
Power Charging	3 w
Power Standby	< 1 W

### EMERGENCY INFORMATION

Test Type	Manual Test
Battery Type	LiFePO4 3.2 V
Recharge Time	24 hrs
Discharge Time	3 hrs
Emergency Classification	C0:D40 C90:D25