

DURA G2

DURA06-G2

SAP CODE: 2002601

Tougher, smarter, and built to last.

Built for performance and designed with flexibility in mind, the DURA G2 batten is the go-to solution for challenging environments such as car parks, warehouses, workshops, and public facilities.

With IP65 and IK08 ratings, flicker-free light output, and a new modular motion sensor kit (available as an accessory) compatible with both standard and emergency models.

APPLICATIONS

Carpark, Carport, Storage Facilities, Storage Rooms, Warehouse, Kitchen/ Food Prep, Balconies/Patios/Verandas, Awnings, Garage, Shed, Side of Building, Manufacturing Facilities, Hangers, Public Facilities, Temporary Installations, General Industrial

DIMENSION DIAGRAMS




Disclaimer

NOTE1*: Based on rated LED design life



PHOTOMETRIC DIAGRAM



Unit: cd
— C0/180 128.0deg
— C90/270 108.2deg

KEY INFORMATION

Power	10 W 13 W 15 W 18 W
Lumen Output	1229 / 1260 / 1189 lm 1591 / 1659 / 1539 lm 1888 / 1986 / 1827 lm 2184 / 2328 / 2107 lm
Mounting Type	Surface Mount / Suspended
Dimming Type	Non-Dimmable
Fascia Colour	Grey
IP Rating	IP65
IK Rating	IK08
Operating Ambient Temp.	-20 to 40°C
Connection Type	PA12 Terminals
Driver	Integral
Warranty	5 yrs

PHOTOMETRIC

Efficacy	10 W: 119 / 126 / 116 lm/W 13 W: 121 / 131 / 118 lm/W 15 W: 119 / 130 / 116 lm/W 18 W: 115 / 129 / 112 lm/W
CCT	4000 / 4500 / 5000 K
CRI	> 80
SDCM	< 5
UGR	< 25
Beam Angle	120°
Flicker-Free	Yes
Projected Lifespan*	>102,000hrs @ Ta 40°C (L70)

ELECTRICAL

Input Voltage	220-240Vac, 50/60Hz
Power Factor	> 0.9
Electrical Classification	Class I
Surge Protection	Overload / Short Circuit

OTHERS

Body Material	Polycarbonate
Diffuser Material	Polycarbonate (Opal)
Cable Entry	Both ends; Top
Rebate Scheme Approvals	
HACCP Approval	Yes
Weight	0.8 kg
Dimensions	655 x 102 x 75 mm