



FOCI^{G2}

LED Track Spotlights

TRITONE
Colour Selectable

24-60°
Beam Angle

0-350°
Adjustment Angle

>90
CRI Colour Rendering Index

80,000hr
Projected Lifespan

5yr
Warranty

Timeless elegant and dynamic.

Experience the versatility and precision of **FOCI G2**, the LED track light that adapts to your lighting needs. With an adjustable beam angle ranging from 24° to 60°, **FOCI G2** delivers focused illumination for tasks or a wider beam for ambient lighting. Its sleek, diecast aluminium construction and ultra-slim driver create a modern, architectural statement.

Features

- Power switchable
- Adjustable gimbal
- Tritone colour selectable
- High Colour Rendering Index (CRI)
- Adjustable Beam Angle

Benefits

- Adjust the light to suit the requirements
- Increased versatility to direct light where it is required
- Provides the choice of light hues from a single luminaire
- True colour definition to highlight natural colour
- Customise your lighting experience with a luminaire that effortlessly adjusts its beam spread.



Product Overview

POWER	LUMENS	EFFICACY	CCT	WEIGHT	SAP CODE	PRODUCT CODE
12 W	12 W: 1241 / 1325 / 1370 lm	12 W: 103 / 110 / 114 lm/W	2700 / 3000 / 4000 K	0.6 kg	2002539	FOCI24W-W
15 W	15 W: 1573 / 1707 / 1733 lm	15 W: 105 / 114 / 116 lm/W			2002538	FOCI24W-B
20 W	20 W: 1874 / 2052 / 2080 lm	20 W: 94 / 103 / 104 lm/W		0.7 kg	2002541	FOCI35W-W
24 W	24 W: 2166 / 2394 / 2373 lm	24 W: 90 / 100 / 99 lm/W			2002540	FOCI35W-B
24 W	24 W: 2473 / 2677 / 2649 lm	24 W: 103 / 112 / 110 lm/W				
28 W	28 W: 2728 / 3031 / 2989 lm	28 W: 97 / 108 / 107 lm/W				
31 W	31 W: 3004 / 3356 / 3244 lm	31 W: 97 / 108 / 105 lm/W				
35 W	35 W: 92 / 105 / 100 lm/W	35 W: 92 / 105 / 100 lm/W				

SPECIFICATIONS				APPLICATIONS
Body Material:	Aluminium	Driver:	Integral	Hallways
Diffuser Material:	Polycarbonate (Clear)	Connection Type:	Universal Track	Retail Spaces
Body Colour:	White Black	Electrical Classification:	Class II	Function Areas
IP Rating:	IP20	Projected Lifespan:	>80,000hrs@Ta25°C(L80)	Cocktail Lounge
Flicker-Free:	Yes	Operating Ambient Temp.	-20 to 35°C	Restaurants / Cafes
Adjustable Angle:	0 - 350°	Power Factor:	> 0.9	
Beam Angle:	24 - 60°	Surge Protection:	Overload / Short Circuit	
SDCM:	< 3	Smart:	KASTA Compatible	
Mounting Type:	Surface Mount	Warranty:	5 yrs	
Dimming:	Non-Dimmable			

Linear and Track Lighting

DIMENSIONS

