

FOCI G2

FOCI24W-B
SAP CODE: 2002538


Timeless elegant and dynamic.

Experience the versatility and precision of FOCI G2, the LED track light that adapts to your lighting needs. With an adjustable beam angle ranging from 24° to 60°, FOCI G2 delivers focused illumination for tasks or a wider beam for ambient lighting. Its sleek, diecast aluminium construction and ultra-slim driver create a modern, architectural statement.


APPLICATIONS

Kitchen / Food Prem, Hallways, Retail Spaces, Function Areas, Cocktail Lounge, Restaurants / Cafes

DIMENSION DIAGRAMS



PHOTOMETRIC DIAGRAM



Unit: cd
 - C0/180,67.3
 - C30/210,67.3

Photometric diagram shown is for 3000 K output.

KEY INFORMATION

| | |
|-------------------------|--|
| Power | 12 W 15 W 20 W 24 W |
| Lumen Output | 1241 / 1325 / 1370 lm 1573 / 1707 / 1733 lm 1874 / 2052 / 2080 lm 2166 / 2394 / 2373 lm |
| Mounting Type | Universal Track |
| Dimming Type | Non-Dimmable |
| Body Colour | Black (RAL9005) |
| Body Material | Aluminium |
| IP Rating | IP20 |
| Operating Ambient Temp. | -20 to 35°C |
| Connection Type | Universal Track |
| Driver | Integral |
| Warranty | 5 yrs |

PHOTOMETRIC

| | |
|--------------|---|
| Efficacy | 12 W: 103 / 110 / 114 lm/W 15 W: 105 / 114 / 116 lm/W 20 W: 94 / 103 / 104 lm/W 24 W: 90 / 100 / 99 lm/W |
| CCT | 2700 / 3000 / 4000 K |
| CRI | > 90 |
| SDCM | < 3 |
| UGR | < 22 |
| Beam Angle | 24 - 60° |
| Flicker-Free | Yes |
| Lifespan | >80,000hrs@Ta25°C(L80) |

ELECTRICAL

| | |
|---------------------------|--------------------------|
| Input Voltage | 220-240Vac 50/60HZ |
| Power Factor | > 0.9 |
| Electrical Classification | Class II |
| Surge Protection | Overload / Short Circuit |

OTHERS

| | |
|-------------------------|-----------------------|
| Adjustable Angle | 0 - 350° |
| Diffuser Material | Polycarbonate (Clear) |
| Rebate Scheme Approvals | |
| Weight | 0.6 kg |
| Dimensions | Ø 72 x 165 mm |