



# FOCI G2

**FOCI35W-W**  
SAP CODE: 2002541


## Timeless elegant and dynamic.

Experience the versatility and precision of FOCI G2, the LED track light that adapts to your lighting needs. With an adjustable beam angle ranging from 24° to 60°, FOCI G2 delivers focused illumination for tasks or a wider beam for ambient lighting. Its sleek, diecast aluminium construction and ultra-slim driver create a modern, architectural statement.


### APPLICATIONS

Kitchen / Food Prem, Hallways, Retail Spaces, Function Areas, Cocktail Lounge, Restaurants / Cafes

### DIMENSION DIAGRAMS



### PHOTOMETRIC DIAGRAM



Unit: cd  
 — C0/180,68.0  
 — C30/210,68.0

Photometric diagram shown is for 3000 K output.

### KEY INFORMATION

Power	24 W 28 W 31 W 35 W
Lumen Output	2473 / 2677 / 2649 lm 2728 / 3031 / 2989 lm 3004 / 3356 / 3244 lm 3219 / 3659 / 3502 lm
Mounting Type	Universal Track
Dimming Type	Non-Dimmable
Body Colour	Black (RAL9005)
Body Material	Aluminium
IP Rating	IP20
Operating Ambient Temp.	-20 to 35°C
Connection Type	Universal Track
Driver	Integral
Warranty	5 yrs

### PHOTOMETRIC

Efficacy	24 W: 103 / 112 / 110 lm/W 28 W: 97 / 108 / 107 lm/W 31 W: 97 / 108 / 105 lm/W 35 W: 92 / 105 / 100 lm/W
CCT	2700 / 3000 / 4000 K
CRI	> 90
SDCM	< 3
UGR	< 22
Beam Angle	24 - 60°
Flicker-Free	Yes
Lifespan	>80,000hrs@Ta25°C(L80)

### ELECTRICAL

Input Voltage	220-240Vac 50/60HZ
Power Factor	> 0.9
Electrical Classification	Class II
Surge Protection	Overload / Short Circuit

### OTHERS

Adjustable Angle	0 - 350°
Diffuser Material	Polycarbonate (Clear)
Rebate Scheme Approvals	
Weight	0.7 kg
Dimensions	Ø 80 x 184 mm