

FLEXION DOTLESS

FXDL14W-4K2M SAP CODE: 2002481


Seamless lighting solution.

For ambient or feature lighting, the new Flexion Dotless range offers integrated lighting solutions that produce bright, effective linear illumination Endless flexibility is provided by the Flexion Dotless series when combined with the complementing Parallax profile range.

APPLICATIONS

Accent / Display / Feature Lighting, Boardroom / Meeting Rooms, Butler Pantry, Cabinetry, Cocktail Lounge, Ensuite, Games Rooms, Hallways, Hotel Rooms, Restaurants / Cafes, Retail Spaces, Showrooms, Staircase, Walk-in Wardrobes, Kitchen / Food Prep, Function Areas

DIMENSION DIAGRAMS



Disclaime

Compatible with all Parallax





KEY INFORMATION	
Power	14W/m
Lumen Output	1470 lm per metre
Cut Length	55 mm
Mounting Type	Self Adhesive Backing
Dimming Type	Non-Dimmable
Fitting Colour	White
IP Rating	IP40
Operating Ambient Temp.	0 to 40°C
Connection Type	450mm flying tail with 1.2m flex and plug
Driver	Remote
Warranty	5 yrs
PHOTOMETRIC	

PHOTOMETRIC	
LED	SOB
Efficacy	110 lm/W
CCT	4000 K
CRI	> 90
SDCM	< 3
Beam Angle	140°
Flicker-Free	No
Projected Lifespan	54,000hrs @ Ta 25° (L70)

ELECTRICAL	
Input Voltage	220-240Vac 50/60HZ
Driver Output Voltage	Not Appllicable
Power Factor	> 0.9
Electrical Classification	Class II
Surge Protection	Overload / Short Circuit

OTHERS	
Weight	0.3 kg
Dimensions	2,000 x 8 x 3 mm