

FLEXION DOTLESS

FXDL6W-3K2M SAP CODE: 2002462

Seamless lighting solution.

For ambient or feature lighting, the new FLEXION DOTLESS range offers integrated lighting solutions that produce bright, effective linear illumination. Endless flexibility is provided when combining the FLEXION DOTLESS series with the new PARALLAX series of complementary aluminium profiles.

APPLICATIONS

Accent / Display / Feature Lighting, Boardroom / Meeting Rooms, Butler Pantry, Cabinetry, Cocktail Lounge, Ensuite, Games Rooms, Hallways, Hotel Rooms, Restaurants / Cafes, Retail Spaces, Showrooms, Staircase, Walk-in Wardrobes, Kitchen / Food Prep, Function Areas



Compatible with all Parallax





| KEY INFORMATION | |
|-------------------------|---|
| Power | 6W/m |
| Lumen Output | 760 lm per metre |
| Cut Length | 55 mm |
| Mounting Type | Self Adhesive Backing |
| Dimming Type | Non-Dimmable |
| Fitting Colour | White |
| IP Rating | IP40 |
| Operating Ambient Temp. | 0 to 40°C |
| Connection Type | 450mm flying tail with 1.2m flex and plug |
| Driver | Remote |
| Warranty | 5 yrs |

| PHOTOMETRIC | |
|--------------------|--------------------------|
| LED | SOB |
| Efficacy | 110 lm/W |
| CCT | 3000 K |
| CRI | > 90 |
| SDCM | < 3 |
| Beam Angle | 140° |
| Flicker-Free | No |
| Projected Lifespan | 54,000hrs @ Ta 25° (L70) |

| ELECTRICAL | |
|---------------------------|--------------------------|
| Input Voltage | 220-240Vac 50/60HZ |
| Driver Output Voltage | 24 Vdc |
| Power Factor | > 0.9 |
| Electrical Classification | Class II |
| Surge Protection | Overload / Short Circuit |

| OTHERS | |
|------------|------------------|
| Weight | 0.3 kg |
| Dimensions | 2,000 x 8 x 3 mm |