




IKON

Residential Downlight



Greenstar compliant meets architectural quality.

IKON is a compact, recessed downlight designed for performance and compliance. With $UGR < 19$, $CRI > 90$, $SDCM < 3$, and a 40mm profile with remote driver, it delivers consistent, comfortable lighting for Greenstar projects and shallow ceiling spaces.

Features

- Glare-free illumination with $UGR < 19$
- High Colour Rendering Index (CRI)
- Dual colour changeable
- IC-4 rating (ta 25°C)
- IP54 rating (from below)
- Low profile design
- Dimmable driver
- Modernised design

Benefits

- Excellent lighting option for indoor work places;
- True colour definition to highlight natural colour;
- Provides the choice of light hues from a single luminaire;
- Allows for covered and abutted installations;
- Suitable for wet rooms such as bathrooms & laundries
- Suitable for very shallow ceiling spaces;
- Adjustable brightness to improve comfort;
- Provides high end appearance;


Product Overview

POWER	LUMENS	EFFICACY	CCT	WEIGHT	SAP CODE	PRODUCT CODE
8 W	772 / 808 lm	107 / 112 lm/W	3000 / 4000 K	0.2 kg	2002623	IKON8W

SPECIFICATIONS

Body Material:	Plastic coated Aluminium	Driver:	Remote	APPLICATIONS Bedrooms Lounge Room Dining Area Laundry Butler Pantry Hallways Entrance Staircase Bathrooms Ensuite Theatre Rooms Games Rooms Hotel Rooms
Diffuser Material:	Polycarbonate Lens	Connection Type:	0.6m Flex & Plug	
Body colour:	White	Input:	220-240Va.c. 50/60Hz	
Fascia colour:	White RAL 9016	Electrical Classification:	Class II	
IP Rating:	IP54 Front	Power Factor:	> 0.9	
Beam Angle:	50°	Protection:	Overload / Short Circuit	
CRI:	> 90	Lifespan:	>102,000hrs@Ta25°C(L70)	
SDCM:	< 3	Operating Ambient Temperature:	-20 to 45°C	
IC Rating:	IC-4	Smart:	KASTA Compatible	
UGR:	<19	Dimming:	Phase-Cut Dimmable	

DIMENSIONS (mm)



Residential Downlights

