



Phase-Cut Trailing Edge Dimmers

Product Name	SOLO	DUOG2	KASTA PUSH BUTTON DIMMER	KASTA MATTER PUSH BUTTON DIMMER	KASTA DIMMER MODULE	KASTA DIMMER SOCKET
Model No.	SOLO350W	DUO350WG2	KASTA-DM300BH-W	KMDIM400	KASTA-D300IBH	KBSKTD350
2-wire / 3-wire / 4-wire / 5-wire	2-wire	2-wire	2-wire	2-wire	3-wire	3-wire
Multiway Control	No	No	Yes KASTA-1BMBH-W KASTA-RB02 H1-6RSMB	Yes KMDIM400 KMREM	Yes KASTA-1BMBH-W KASTA-RB02 H1-6RSMB	Yes KASTA-1BMBH-W KASTA-RB02 H1-6RSMB
Configurable LED Indicator	No	Yes	Yes, through KASTA app	Yes	No	No
Configurable Min Brightness	No	Yes	Yes, through KASTA app	Yes	Yes, through KASTA app	Yes, through KASTA app
Min. Load	7W	7W	6W	2W	6W	7W
Max. Load	350W	350W	300W	400W	300W	350W
Timer Range	N/A	30 Mins countdown	Yes, through KASTA app 30 Mins countdown	N/A	Yes, through KASTA app	Yes, through KASTA app
Built In Protection	Overcurrent Overtemperature Short-circuit protection	Overcurrent Overtemperature Short-circuit protection	Overcurrent	Overcurrent Overtemperature Short-circuit protection	Overcurrent	Overcurrent
Depth from Grid Compatible Wallbox	29mm Standard	29mm Standard	29mm Standard	29mm Standard	Switchplate dependant	N/A
No. Units in a Plate	6 (derating applies)	6 (derating applies)	6 (derating applies)	6 (derating applies)	6 (wired to bell press switches)	6 (wired to bell press switches)
Applications	Dimmable LEDs Incandescent Halogen Lighting	Dimmable LEDs Incandescent Halogen Lighting	Dimmable LEDs Incandescent Halogen Lighting	Dimmable LEDs Incandescent Halogen Lighting	Dimmable LEDs Incandescent Halogen Lighting	Dimmable LEDs Incandescent Halogen Lighting

Lighting Control Selection Chart



0/1-10V Dimmers

GENIE	KASTA 0-10V DIMMER MODULE	KASTA 0-10V DIMMER HIGHBAY
GN10VDIM-W	KASTA-D1-10VIB	D1-10VIBH
2-wire	4-wire	5-wire
No	Yes KASTA-1BMBH-W KASTA-RB02 H1-6RSMB	Yes KASTA-1BMBH-W KASTA-RB02 H1-6RSMB
No	No	No
Yes	No	No
N/A	N/A	N/A
N/A (Max 30 drivers)	N/A (Max 30 drivers)	N/A (Max 30 drivers)
N/A	Yes, through KASTA app	N/A
Overcurrent Overtemperature Short-circuit protection	Overtemperature	Overtemperature
20mm Standard	Switchplate dependant	N/A
6	6 (wired to bell press switches)	N/A
Dimmable 0/1-10V lighting	Dimmable 0/1-10V lighting	Dimmable 0/1-10V lighting