KASTA

Installation Instructions

Smart Remote Switch 5-Input Module

Product Code:
KASTA-5RSIBH

APP Installation
Visit www.kasta.com.au or your app store to download the free KASTA app.
iOS: requires iOS 9.0 or later.
Android: requires Android 4.4 or later.
Devices must support Bluetooth 4.0

Download on the App Store

ANDROID APP ON Google play

Important Safety Information

- This product must be installed by a licensed electrician in accordance with all the require ments of AS/NZS 3000 (current edition) and other relevant Standards and Regulations.
- Electricity MUST be disconnected prior to installation. Failure to do so may result in serious injury and or loss of life.
- Indoor use only. Not suitable for damp or explosive environments.
- Complies to Australian Standards AS/NZS 60950.1:2015, AS/NZS CISPR 15.
- No user serviceable parts inside.

FEATURES

- Mains powered remote switch input module with five separate inputs.
- Pair with and control other KASTA devices.
- Simple 7 wire connection – A, N, S1, S2, S3, S4, S5.
- 2 modes of operation.
  - Mode 1: TOGGLE INPUT
    Wirelessly control KASTA devices, groups and scenes when a toggle/latching output from a PIR sensor is activated. Install in conjunction with a device (e.g. PIR sensor) to terminal S1-5 (default mode).
  - Mode 2: MOMENTARY SWITCH INPUT
    Wirelessly control KASTA Devices, Groups and Scenes from short press or long press of a momentary switch mechanism. Install in conjunction with an appropriately rated mo mentary action mechanism to S1-5 terminal (select momentary input mode in the KASTA app).
- Can be paired with KASTA devices for multi-way control (8x maximum).
- Built in overvoltage protection.
- To prevent a reduction in Bluetooth®signal strength, install away from metal objects.
- Patent No. 2019101685, 201921256952.4.

FUNCTION SETUP
S1, S2, S3, S4, S5 TOGGLE INPUT MODE
Load output from a PIR sensor will trigger the on/off function of paired KASTA deveices.

ON/OFF SWITCH	1 CLICK

Turns device on or off.

S1, S2, S3, S4, S5 MOMENTARY SWITCH INPUT MODE

ON/OFF	1 CLICK

Turns paired device on or off. When paired with a dimmable light, light will adjust to previous brightness level.

DIM UP/DOWN	ONE LONG PRESS

When paired with a light, long press button to dim up or down.
Release button to stop.

FULL BRIGHTNESS	2 CLICKS

When paired with a light, sets lights to full brightness.

DELAY TO OFF	3 CLICKS*

Paired device turns off automatically after a set time (configured in the app).
Single click to cancel.

VARIABLE	4 CLICKS

Refer to the paired device for functionality.

VARIABLE	5 CLICKS

Refer to the paired device for functionality.

FACTORY RESET	9 CLICKS OF 'RESET' BUTTON*

Restores all settings back to factory.
*If successful, the LED indicator will flash the number of times it was clicked.

APP ENABLED FUNCTION

RETRIGGER TIMER	1 CLICK

Commence time (on/off). Function must be programmed through the KASTA app first.

TECHNICAL SPECIFICATIONS

Operating Temp: -20ºc to 40ºc	
Supply: 220-240V AC 50Hz	

KASTA

Installation Instructions

CONNECTION DIAGRAM

A
N

A N LOAD
SENSOR

AC INPUT
S1 S2 S3 S4 S5

REPEAT FOR S2-S5 INPUT AS REQUIRED

A
N

AC INPUT
S1 S2 S3 S4 S5

REPEAT FOR S2-S5 INPUT AS REQUIRED

Smart Remote Switch 5-Input Module

Product Code:
KASTA-5RSIBH

APP Installation

Visit www.kasta.com.au or your app store to download the free KASTA app.
iOS: requires iOS 9.0 or later.
Android: requires Android 4.4 or later.
Devices must support Bluetooth 4.0

Download on the
App Store

ANDROID APP ON
Google play

Important Safety Information

• This product must be installed by a licensed electrician in accordance with all the require ments of AS/NZS 3000 (current edition) and other relevant Standards and Regulations.
• Electricity MUST be disconnected prior to installation. Failure to do so may result in serious injury and or loss of life.
• Indoor use only. Not suitable for damp or explosive environments.
• Complies to Australian Standards AS/NZS 60950.1:2015, AS/NZS CISPR 15.
• No user serviceable parts inside.