


Installation Instructions



KASTA Smart Downlights

Product Code:
KB12TWD1-WH
KB12RGBTWD1-WH

APP Installation

Visit www.kasta.com.au or your app store to download the free KASTA app.
 iOS: requires iOS 9.0 or later.
 Android: requires Android 4.4 or later.
 Devices must support Bluetooth 4.0



Important Safety Information

- This product must be installed by a licensed electrician in accordance with all the requirements of AS/NZS 3000 (current edition) and other relevant Standards and Regulations.
- Electricity MUST be disconnected prior to installation. Failure to do so may result in serious injury and or loss of life.
- Indoor use only. Not suitable for damp or explosive environments.
- Complies to Australian Standards AS/NZS60598.2.2.
- No user serviceable parts inside.
- Not suitable for use with standard in-wall dimmers. Dimmable via the KASTA app only.
- Building insulation used to abut and cover the luminaire must meet the following requirements:
 - 1: Be of a type that can maintain its dimensions and structural integrity when exposed to the maximum surface temperatures of the class of luminaire, being 90 Degree Celsius and must withstand a 30s needle flame test carried out in accordance with AS/NZS 60695.11.5 with the flame applied to all surfaces of the sample.
 - 2: Loose fill insulation is permitted to abut or cover this luminaire.

FEATURES

- Tuneable White LED Downlight.
- RGB and Tuneable White LED Downlight.
- 110mm diameter white trim.
- 90mm cut-out.
- Remote driver with flex and plug.
- IC-4 rated (AU) and IC-F rated (NZ).
- Wireless Bluetooth® Mesh communication.
- Control from the KASTA app or KASTA remote switch devices (8x maximum per downlight).
- On, off, dim and button press functions from local button (remote driver) or KASTA remote switch devices.
- Configured using the KASTA app (iOS and Android), with a white CCT dial, a RGB colour wheel and a pre-set colour palette.
- Supports Group, Scene, Timer and Scheduling automation functions.
- 3 year warranty.

FUNCTION SETUP

(Controllable via KASTA remote switch devices or the RESET button on the LED Driver)

ON/OFF	1 CLICK
Turns lights on or off. When turned ON, lights will adjust to previous brightness setting.	
DIM UP/DOWN	ONE LONG PRESS
When lights are on, long press button to dim up or down. Release button to stop.	
FULL BRIGHTNESS	2 CLICKS
Sets lights to full brightness.	
DELAY TO OFF	3 CLICKS*
Light turns off automatically after a set time (configured in the app). Single click to cancel.	
SET WHITE CCT COLOUR TEMPERATURE	4 CLICKS*
Cycle through white CCT colour temperature. Click button 1 time to store setting.	
SET RGB COLOUR	5 CLICKS*
Cycle through the pre-set colours to your desired colour. Click button 1 time to store setting.	
FACTORY RESET	9 CLICKS

Restores all settings back to factory (using reset button only).
 *If successful, light will pulse the number of times that the switch was clicked, indicating function.

TECHNICAL SPECIFICATIONS

RGB & CCT: RGB: 16M colours
 White: 2700K - 6500K

CRI: ≥80 (for White)

Supply: 220-240V AC 50Hz

Operating Temp: -20°C to 40°C (IC-4 Max 25°C)

Input Power: Max 12W +/- 10% (White)

IP Rating: IP44 (light-emitting area)
 IP40 (main body)

Dimensions: 125x51x44mm

CONNECTION DIAGRAM

