

LUME

LUME1WD40
SAP CODE: 2002009

A reliable path to building safety

LUME is a sleek, emergency luminaire suitable for a large variety of applications, due to its recessed and surface mounting options. Using reliable lithium iron phosphate (LiFePo4 3.2V) battery technology, this state-of-the-art product ensures low maintenance and energy efficiency.

APPLICATIONS

Laundry, Hallways, Entrance, Staircase, Bathrooms, Theatre Rooms, Showrooms, Offices, Boardroom / Meeting Rooms, Function Areas, Education Facilities, Retail Spaces, Restaurants / Cafes, Storage Rooms, Kitchen / Food Prep

DIMENSION DIAGRAMS



KEY INFORMATION

Power	1.5 W
Lumen Output	193 lm
Viewing Distance	193 lm
Mounting Type	Recessed
Body Colour	White
IP Rating	IP20
IK Rating	Not applicable
Operating Ambient Temp.	0 to 40°C
Connection Type	1m Flex & Plug
Warranty	5 yrs
Battery Warranty	1yr

PHOTOMETRIC

CCT	5700 K
CRI	> 80
Beam Angle	150°

ELECTRICAL

Input Voltage	220-240Vac, 50/60Hz
Electrical Classification	Class II
Power Charging	1.5 W
Power Standby	0.5 W
Surge Protection	Overload / Short Circuit

EMERGENCY INFORMATION

Test Type	Self / Manual Test
Battery Type	LiFePo4 3.2V
Recharge Time	16 hrs
Discharge Time	1.5 hrs
Emergency Classification	C0:D40 C90: D40

OTHERS

Body Material	Polycarbonate
Diffuser Material	PolyCarbonate (Clear)
Weight	0.3 kg
Dimensions	Ø110 x 49 mm