



METEOR EVO

M16W160R-EV

SAP CODE: 2002630

Slim, diffuser design


METEOR EVO is a surface mounted tubular luminaire featuring with durable UV stabilized polycarbonate body and an opal diffuser that delivers uniform, soft illumination.

Designed for visual comfort and aesthetic versatility, it is ideal for corridors, entries, balconies, benchtops, and general ceiling-mounted lighting.


APPLICATIONS

Walk-in Wardrobes, Function Areas
Balconies / Patios / Verandahs,
Bathrooms, Cocktail Lounges, Entrances,
Food Courts, Showrooms, Restaurants /
Cafes

DIMENSION DIAGRAMS



PHOTOMETRIC DIAGRAM



Unit: cd

— C0/180 111.9deg

— C90/270 110.9deg

Photometric diagram shown is for 4000K output.

KEY INFORMATION

Power	14 / 16 W
Lumen Output	14W: 1482 / 1566 / 1459 lm 16W: 1631 / 1794 / 1760 lm
Cutout Size	Not Applicable
Mounting Type	Surface Mount
Dimming Type	Phase-Cut Dimmable (Trailing Edge, 1-100%)
Body Colour	White
IP Rating	IP54
IC Rating	Not Applicable
Operating Ambient Temp.	-20 to 40°C
Connection Type	PA16
Driver	Integral
Warranty	5 yrs

PHOTOMETRIC

Efficacy	14W: 105 / 117 / 110 lm/W 16W: 102 / 117 / 110 lm/W
CCT	3000 / 4000 / 5000 K
CRI	> 80
SDCM	<6
UGR	Not Applicable
Beam Angle	110°
Flicker-Free	Yes
Projected Lifespan	102,000 hrs @25°C L80

ELECTRICAL

Input Voltage	220-240Vac, 50-60Hz
Driver Output Voltage	55-78VDC
Driver Output Current	175/200 mA
Power Factor	> 0.9
Electrical Classification	Class II
Surge Protection	Overload / Short Circuit

OTHERS

Adjustable Angle	Not Applicable
Body Material	UV Stabilized Polycarbonate
Diffuser Material	Polycarbonate
Rebate Scheme Approvals	Not Applicable
HACCP Approval	Pending
Weight	0.35 kg
Dimensions	Ø160 x 52 mm

Disclaimer

NOTE 1: Based on rated LED design lifetime