



METEOR EVO

M6W90R-EV

SAP CODE: 2002626


Slim, diffuser design

METEOR EVO is a surface mounted tubular luminaire featuring with durable UV Stabilized polycarbonate body and an opal diffuser that delivers uniform, soft illumination. Designed for visual comfort and aesthetic versatility, it is ideal for corridors, entries, balconies, benchtops, and general ceiling-mounted lighting.


APPLICATIONS

Walk-in Wardrobes, Function Areas
Balconies / Patios / Verandahs,
Bathrooms, Cocktail Lounges, Entrances,
Food Courts, Showrooms, Restaurants /
Cafes

DIMENSION DIAGRAMS



PHOTOMETRIC DIAGRAM



Unit: cd
 - C0/180 114.5deg
 - C90/270 114.5deg
 Photometric diagram shown is for 4000K output.

KEY INFORMATION

Power	4 / 6 W
Lumen Output	4W: 414 / 426 / 430 lm 6W: 627 / 627 / 632 lm
Cutout Size	Not Applicable
Mounting Type	Surface Mount
Dimming Type	Phase-Cut Dimmable (Trailing Edge, 1-100%)
Body Colour	White
IP Rating	IP54
IC Rating	Not Applicable
Operating Ambient Temp.	-20 to 40°C
Connection Type	PA12
Driver	Integral
Warranty	5 yrs

PHOTOMETRIC

Efficacy	4W: 107 / 112 / 112 lm/W 6W: 115 / 117 / 116 lm/W
CCT	3000 / 4000 / 5000 K
CRI	> 80
SDCM	<6
UGR	Not Applicable
Beam Angle	110°
Flicker-Free	Yes
Projected Lifespan	102,000 hrs @25°C L80

ELECTRICAL

Input Voltage	220-240Vac, 50-60Hz
Driver Output Voltage	55-78VDC
Driver Output Current	50/70 mA
Power Factor	> 0.9
Electrical Classification	Class II
Surge Protection	Overload / Short Circuit

OTHERS

Adjustable Angle	Not Applicable
Body Material	UV Stabilized Polycarbonate
Diffuser Material	Polycarbonate
Rebate Scheme Approvals	Not Applicable
HACCP Approval	Pending
Weight	0.19 kg
Dimensions	Ø90 x 52 mm

Disclaimer

NOTE 1: Based on rated LED design lifetime