



MATRIX^{EVO} G2

Panels

Streamlined solution, competitive value.

Introducing the **MATRIX^{EVO} G2**, the ultimate lighting solution for discerning businesses. This highly efficient, tritone selectable backlit panel offers unparalleled versatility and performance, making it a perfect fit for any workspace.

Features

- Tritone colour selectable
- Power switchable
- Flicker-free driver
- Low profile design
- Modernised design
- Adaptable mounting possibilities
- Choice of sizes to choose from
- High ambient temperature rating (>40°C)
- Optional DALI model available

Benefits

- Provides the choice of light hues from a single luminaire.
- Adjust the light to suit the requirements.
- Increase productivity and lowers eye strain
- Suitable for very shallow ceiling spaces.
- Provides high end appearance.
- Choose which mounting option best suits the application.
- Adaptable to suit various requirements.
- Long lasting in hot environments.
- Designed to integrate into a larger ecosystems.



Product Overview

POWER	LUMENS	EFFICACY	CCT	WEIGHT	SAP CODE	PRODUCT CODE
28 W	2810 / 3175 / 2910 lm	110 / 125 / 119 lm/W	3000 / 4000 / 5000 K	1.65 kg	2002707	MATX0312-EV-G2
36 W	3566 / 3969 / 3820 lm	106 / 122 / 115 lm/W				
40 W	3911 / 4384 / 4192 lm	101 / 118 / 108 lm/W				
28 W	2956 / 3249 / 3178 lm	109 / 125 / 117 lm/W	3000 / 4000 / 5000 K	1.65 kg	2002708	MATX0606-EV-G2
36 W	3664 / 4073 / 3929 lm	104 / 122 / 112 lm/W				
40 W	4106 / 4498 / 4312 lm	102 / 118 / 109 lm/W				

SPECIFICATIONS

Body Material:	Steel
Diffuser Material:	PMMA
Body colour:	White
Fascia colour:	White RAL 9003
IP Rating:	IP40
Beam Angle:	90°
CRI:	> 80
SDCM:	< 5
UGR:	< 19
Flicker-free:	Yes
Mounting Type	Metric T-Bar Ceiling Grid

Driver:	Remote
Connection Type:	DC Connector 1.2m Flex & Plug
Input:	220-240Va.c. 50/60Hz
Electrical Classification:	Class II
Power Factor:	> 0.9
Protection:	Overload / Short Circuit
Lifespan:	>54,000hrs@Ta25°C(L70)
Operating Ambient Temperature:	-20 to 45°C
Smart:	KASTA Compatible

Dimming:	Non-Dimmable
----------	--------------

APPLICATIONS

Showrooms
Offices
Boardroom / Meeting Rooms
Function Areas
Education Facilities

DIMENSIONS (mm)

