



MATRIX^{EVO}

Panels

Streamlined solution, competitive value.

Introducing the **MATRIX EVO**, the ultimate lighting solution for discerning businesses. This highly efficient, tri-tone selectable backlit panel offers unparalleled versatility and performance, making it a perfect fit for any workspace.

Features

- Tritone colour selectable
- Power switchable
- Flicker-free driver
- Low profile design
- Modernised design
- Adaptable mounting possibilities
- Choice of sizes to choose from
- High ambient temperature rating (>40°C)
- Optional DALI model available

Benefits

- Provides the choice of light hues from a single luminaire.
- Adjust the light to suit the requirements.
- Increase productivity and lowers eye strain
- Suitable for very shallow ceiling spaces.
- Provides high end appearance.
- Choose which mounting option best suits the application.
- Adaptable to suit various requirements.
- Long lasting in hot environments.
- Designed to integrate into a larger ecosystems.



Product Overview

POWER	LUMENS	EFFICACY	CCT	WEIGHT	SAP CODE	PRODUCT CODE
28 W	3000 / 3360 / 3210 lm	109 / 124 / 115 lm/W	3000 / 4000 / 5000 K	1.85 kg	2002451	MATX0312-EV
32 W	3374 / 3832 / 3623 lm	108 / 127 / 112 lm/W				
36 W	3946 / 4201 / 4290 lm	109 / 123 / 118 lm/W				
40 W	4222 / 4695 / 4514 lm	108 / 126 / 117 lm/W				
28 W	3249 / 3521 / 3284 lm	113 / 128 / 112 lm/W	3000 / 4000 / 5000 K	1.65 kg	2002452	MATX0606-EV
32 W	3647 / 4025 / 3696 lm	109 / 126 / 107 lm/W				
36 W	3948 / 4400 / 3984 lm	106 / 124 / 104 lm/W				
40 W	4269 / 4800 / 4280 lm	103 / 122 / 100 lm/W				
28 W	3000 / 3360 / 3210 lm	109 / 124 / 115 lm/W	3000 / 4000 / 5000 K	1.85 kg	2002453	MATX0312-25-EV
28 W	3249 / 3521 / 3284 lm	113 / 128 / 112 lm/W				

SPECIFICATIONS

Body Material:	Steel
Diffuser Material:	PMMA
Body colour:	White
Fascia colour:	White RAL 9003
IP Rating:	IP40
Beam Angle:	110°
CRI:	> 80
SDCM:	< 5
UGR:	< 20
Flicker-free:	Yes
Mounting Type	Metric T-Bar Ceiling Grid

Driver:	Remote
Connection Type:	DC Connector
Input:	220-240Va.c. 50/60Hz
Electrical Classification:	Class II
Power Factor:	> 0.9
Protection:	Overload / Short Circuit
Lifespan:	>54,000hrs@Ta25°C(L70)
Operating Ambient Temperature:	-20 to 45°C
Smart:	KASTA Compatible

Dimming: Non-Dimmable

APPLICATIONS

- Showrooms
- Offices
- Boardroom / Meeting Rooms
- Function Areas
- Education Facilities

Panels

DIMENSIONS (mm)

MATX0606-EV & MATX0606-25-EV



MATX0312-EV & MATX0312-25-EV

