

MATRIX EVO

MATX0606-25-EV
SAP CODE: 2002454


Streamlined solution, competitive Value.

Introducing the MATRIX EVO, the ultimate lighting solution for discerning businesses. This highly efficient, tritone selectable backlit panel offers unparalleled versatility and performance, making it a perfect fit for any workspace.


APPLICATIONS

Showrooms, Offices, Boardroom / Meeting Rooms, Function Areas, Education Facilities, Storage Rooms

DIMENSION DIAGRAMS



PHOTOMETRIC DIAGRAM



Unit: cd

— C0/180,112.9

— C90/270,113.5

Photometric diagram shown is for 4000 K output.

KEY INFORMATION

Power	28 W
Lumen Output	3249 / 3521 / 3284 lm
Mounting Type	Metric T-Bar Ceiling Grid
Dimming Type	Non-Dimmable
Fascia Colour	White RAL9003
IP Rating	IP40
Operating Ambient Temp.	-20 to 40°C
Connection Type	DC Connector
Driver	Remote
Warranty	5 yrs

PHOTOMETRIC

Efficacy	113 / 128 / 112 lm/W
CCT	3000 / 4000 / 5000 K
CRI	> 80
SDCM	< 5
UGR	< 22
Beam Angle	110°
Flicker-Free	Yes
Projected Lifespan	>54,000hrs @ Ta 25°C (L70)

ELECTRICAL

Input Voltage	220-240Vac, 50/60Hz
Driver Output Voltage	25-40V
Driver Output Current	700 mA
Power Factor	> 0.9
Electrical Classification	Class II
Surge Protection	Overload / Short Circuit

OTHERS

Body Material	Steel
Diffuser Material	PMMA
Rebate Scheme Approvals	Not Applicable
Weight	1.65 kg
Dimensions	595 x 595 x 33 mm