



METEOR^{EVO}

Surface Mount Commercial Downlights



Slim, diffuser design.

METEOR EVO is a surface mounted tubular luminaire featuring an opal diffuser that delivers uniform, soft illumination. Designed for visual comfort and aesthetic versatility, it is ideal for corridors, entries, balconies, benchtops, and general ceiling-mounted lighting.

Features

- Tritone colour changeable
- IP54 rating
- Practical performance with a sleek profile.
- Multifaceted reflector
- High colour rendering index (CRI)
- Surface-mounted tubular luminaire with opal diffuser

Benefits

- Provides the choice of light hues from a single luminaire
- Suitable for wet rooms such as bathrooms & laundries
- Reliable performance while maintaining a slim, stylish design
- Greatly reduces glare whilst increasing visibility brilliance
- True colour definition to highlight natural colour
- Provides soft, uniform illumination for visual comfort

Product Overview

POWER	LUMENS	EFFICACY	CCT	WEIGHT	FASCIA	SAP CODE	PRODUCT CODE
6 W	4W: 414 / 426 / 430 lm 6W: 627 / 627 / 632 lm	4W: 107 / 112 / 112 lm/W 6W: 115 / 117 / 116 lm/W	3000 / 4000 / 5000 K	0.2 kg	White	2002626	M6W90R-EV
12 W	10W: 926 / 1000 / 951 lm 12W: 1077 / 1200 / 1131 lm	10W: 103 / 117 / 108 lm/W 12W: 98 / 115 / 104 lm/W	3000 / 4000 / 5000 K	0.3 kg	White	2002628	M12W125R-EV
16 W	14W: 1482 / 1566 / 1459 lm 16W: 1631 / 1794 / 1760 lm	14W: 105 / 117 / 110 lm/W 16W: 102 / 117 / 110 lm/W	3000 / 4000 / 5000 K	0.4 kg	White	2002630	M16W160R-EV
22 W	18W: 2158 / 2243 / 2189 lm 22W: 2485 / 2656 / 2602 lm	18W: 117 / 127 / 122 lm/W 22W: 115 / 126 / 120lm/W	3000 / 4000 / 5000 K	0.55 kg	White	2002632	M22W220R-EV

SPECIFICATIONS

Body Material:	Polycarbonate
Diffuser Material:	Polycarbonate
Reflector:	Multifaceted
Fascia Colour:	White: RAL 9016
IP Rating:	Front: IP54 Body: IP54
Beam Angle:	110 °
Flicker Free:	Yes
CRI:	> 80
SDCM:	< 6

Driver:	Integral
Power Connection:	PA Terminals
Input:	220-240 V, 50 / 60 Hz
Electrical Classification:	Class II
Power Factor:	> 0.9
Lifespan*:	102,000 hrs @25°C L80*
Operating Ambient Temperature:	-20 to 40 °C
Smart:	KASTA Compatible
Dimming:	Phase-Cut Dimmable (Trailing Edge, 10-100%)

APPLICATIONS

- Entrance
- Bathroom
- Balconies / Patios / Verandah
- Awnings
- Garage
- Walk-in Wardrobes
- Hallways
- Hotel Common Areas
- Function Areas
- Kitchen / Food Prep
- Food Courts
- Restaurants / Café's
- Cocktail Lounge

* Based on rated LED design life

DIMENSIONS (mm)

Product Code:	M6W90R-EV	M12W125R-EV	M16W160R-EV	M22W220R-EV
Diameter:	Ø 90 mm	Ø 120 mm	Ø 160 mm	Ø 220 mm
Height:	52 mm	52 mm	52 mm	52 mm

