



METEOR^{EVO}

Surface Mount Commercial Downlights



Slim, diffuser design.

METEOR EVO is a surface mounted tubular luminaire featuring an opal diffuser that delivers uniform, soft illumination. Designed for visual comfort and aesthetic versatility, it is ideal for corridors, entries, balconies, benchtops, and general ceiling-mounted lighting.

Features

- Tritone colour changeable
- IP54 rating
- Practical performance with a sleek profile.
- Multifaceted reflector
- High colour rendering index (CRI)
- Surface-mounted tubular luminaire with opal diffuser

Benefits

- Provides the choice of light hues from a single luminaire
- Suitable for wet rooms such as bathrooms & laundries
- Reliable performance while maintaining a slim, stylish design
- Greatly reduces glare whilst increasing visibility brilliance
- True colour definition to highlight natural colour
- Provides soft, uniform illumination for visual comfort

Product Overview

POWER	LUMENS	EFFICACY	CCT	WEIGHT	FASCIA	SAP CODE	PRODUCT CODE
6 W	4W: 414 / 426 / 430 lm 6W: 627 / 627 / 632 lm	4W: 107 / 112 / 112 lm/W 6W: 115 / 117 / 116 lm/W	3000 / 4000 / 5000 K	0.2 kg	White Black	2002626 2002627	M6W90R-EV M6W90R-EV-BK
12 W	10W: 926 / 1000 / 951 lm 12W: 1077 / 1200 / 1131 lm	10W: 103 / 117 / 108 lm/W 12W: 98 / 115 / 104 lm/W	3000 / 4000 / 5000 K	0.3 kg	White Black	2002628 2002629	M12W125R-EV M12W125R-EV-BK
16 W	14W: 1482 / 1566 / 1459 lm 16W: 1631 / 1794 / 1760 lm	14W: 105 / 117 / 110 lm/W 16W: 102 / 117 / 110 lm/W	3000 / 4000 / 5000 K	0.4 kg	White Black	2002630 2002631	M16W160R-EV M16W160R-EV-BK
22 W	18W: 2158 / 2243 / 2189 lm 22W: 2485 / 2656 / 2602 lm	18W: 117 / 127 / 122 lm/W 22W: 115 / 126 / 120lm/W	3000 / 4000 / 5000 K	0.55 kg	White Black	2002632 2002633	M22W220R-EV M22W220R-EV-BK

SPECIFICATIONS

Body Material:	Polycarbonate	Driver:	Integral
Diffuser Material:	Polycarbonate	Power Connection:	PA Terminals
Reflector:	Multifaceted	Input:	220-240 V, 50 / 60 Hz
Fascia Colour:	White Black	Electrical Classification:	Class II
IP Rating:	Front: IP54 Body: IP54	Power Factor:	> 0.9
Beam Angle:	110°	Lifespan*:	102,000 hrs @25°C L80*
Flicker Free:	Yes	Operating Ambient Temperature:	-20 to 40°C
CRI:	> 80	Smart:	KASTA Compatible
SDCM:	< 6	Dimming:	Phase-Cut Dimmable (Trailing Edge, 10-100%)

APPLICATIONS

Entrance
Bathroom
Balconies / Patios / Verandah
Awnings
Garage
Walk-in Wardrobes
Hallways
Hotel Common Areas
Function Areas
Kitchen / Food Prep
Food Courts
Restaurants / Café's
Cocktail Lounge

* Based on rated LED design life

DIMENSIONS (mm)				
Product Code:	M6W90R-EV M6W90R-EV-BK	M12W125R-EV M12W125R-EV-BK	M16W160R-EV M16W160R-EV-BK	M22W220R-EV M22W220R-EV-BK
Diameter:	Ø 90 mm	Ø 120 mm	Ø 160 mm	Ø 220 mm
Height:	52 mm	52 mm	52 mm	52 mm

