

OXFORD PLUS

OXFORDPLUS12
SAP CODE: 2002718



Premium and low glare

Designed for modern educational environments, the Education Facility LED Batten delivers uniform, low-glare illumination to create a comfortable learning experience. Featuring high efficiency, long service life and reliable performance, it is ideal for classrooms, libraries, corridors and other indoor applications.

APPLICATIONS

Education Facilities, Offices,
Storage Facilities,
Manufacturing Facilities, Indoor
Recreation, General Industrial

DIMENSION DIAGRAMS

KEY INFORMATION

Power	23/30/35/40W
Lumen Output	23W: 2760 lm 30W: 3600 lm 35W: 34200 lm 40W: 4800 lm
Mounting Type	Surface Mount
Dimming Type	DALI Dimmable
Fascia Colour	WHITE 9016
IP Rating	IP20
IK Rating	Not applicable
Operating Ambient Temp.	-20 to 40°C
Connection Type	PA12 Terminals
Driver	Integral
Warranty	5 yrs

PHOTOMETRIC

Efficacy	120 lm/W
CCT	4000 K
CRI	> 90
SDCM	<3
UGR	<19 (23W, 30W)
Beam Angle	90°
Flicker-Free	Yes
Projected Lifespan	>50,000hrs @ 25°C (L70)

ELECTRICAL

Input Voltage	220-240Vac 50/60HZ
Power Factor	> 0.9
Electrical Classification	Class I
Surge Protection	Overload / Short Circuit

OTHERS

Body Material	Steel
Diffuser Material	Polycarbonate (Opal)
Cable Entry	Rear
Rebate Scheme Approvals	NA
Greenstar	Yes
Weight	3.5 kg
Dimensions	1245 x 200 x 45 mm

Disclaimer

NOTE1; This is preliminary datasheet