

*Optional PIR Motion Sensor sold separately.

PROXIMA-PIR-B

PROXIMA^{G2}

Security Spotlight















Sleek and robust.

Experience the versatility and power of **PROXIMA G2**, a customisable and robust outdoor security lighting solution featuring flexible 360° pivot rotation and quick toolless installation. Available as a single or twin lamp, **PROXIMA G2** seamlessly blends into any residential or commercial outdoor space, offering a sleek and stylish design.

Features

- Tritone colour selectable
- IP54 and IK10 ratings
- Toolless, hassle-free installation
- Quick and effortless adjustability
- *Optional plug-in motion sensor

Benefits

- Provides the choice of light hues from a single luminaire
- Ideal for outdoor applications
- Speeds up the process and eliminates the need for extra tools
- Allows easy lighting adjustments with minimal effort
- Save on power consumption when not in use

PROXIMA^{G2}

Product Overview





POWER	LUMENS	EFFICACY	сст	WEIGHT	SAP CODE	PRODUCT CODE
12 W	925 / 1087 / 1021 lm	77 / 96 / 86 lm/W	3000 / 4000 / 5700 K	0.6 kg	2002529	PROXIMA-12
24 W	1691 / 2098 / 1973 lm	70 / 92 / 83 lm/W	3000 / 4000 / 5700 K	0.8 kg	2002530	PROXIMA-24


SPECIFICATIONS					
Body Material:	Aluminium and ABS	Driver:	Integral		
Diffuser Material:	PMMA (Acrylic)	Connection Type:	PA12 Terminal Block		
Body Colour:	Black (RAL9005)	Electrical Classification:	Class I		
IP Rating:	IP54	Projected Lifespan:	>50,000hrs@Ta25°C(L80)		
IK Rating:	IK10	Operating Ambient Temp.	0 to 40°C		
Beam Angle:	120°	Power Factor:	> 0.5		
SDCM:	<3	Surge Protection:	Overload / Short Circuit		
Mounting Type:	Surface Mount	Smart:	KASTA Compatiable		
Dimming:	Non-Dimmable				


APPLICATIONS	
Shed	
Carpark	
Carport	
Side of Building	
Area Lighting	

DIMENSIONS









PROXIMA-12 PROXIMA-24

ACCESSORIES



Description	Product Code
PIR Motion Sensor	PROXIMA-PIR-B

SENSOR SPECIFICATION

Detection Range	160°	
Ambient Light	10-2000LUX (Adjustable)	
Time Delev	Minimum: 10sec ± 3sec	
Time Delay	Maximum: 12min ± 2min	
Detection Motion Speed	0.6876 - 1.5m/s	
Detection Distance	2 - 12m (adjustable)	
Working Temperature	-20 to 40°C	
Working Humidity	<93% RH	
IP Rating	IP54	
Warranty	3 yrs	

