

PROXIMA G2

PROXIMA-24 SAP CODE: 2002530

Sleek and robust


Experience the versatility and power of PROXIMA G2, a customisable and robust outdoor security lighting solution featuring flexible 360° pivot rotation and quick toolless installation.

Available as a single or twin lamp, PROXIMA G2 seamlessly blends into any residential or commercial outdoor space, offering a sleek and stylish design.

APPLICATIONS


Shed, Carpark, Carport, Side of Building, Area Lighting

DIMENSION DIAGRAMS





PHOTOMETRIC DIAGRAM



Unit: cd

- -C0/180 93.9deg
- -C30/210 94.1deg
- -C60/240 93.2deg
- C90/270 92.5deg

KEY INFORMATION	
Power	12W
Lumen Output	1691 / 2098 / 1973 lm
Mounting Type	Surface Mount
Dimming Type	Non-Dimmable
Body Colour	Black (RAL9005)
IP Rating	IP54
IK Rating	IK10
Operating Ambient Temp.	0 to 40°C
Connection Type	PA12 Terminal Block
Driver	Integral
Warranty	3 yrs

Driver	Integral
Warranty	3 yrs
PHOTOMETRIC	
Efficacy	70 / 92 / 83 lm/W
CCT	3000 / 4000 / 5700 K
CRI	> 80
SDCM	< 5
Beam Angle	120°
Flicker-Free	No
Projected Lifespan	>50,000hrs@Ta25°C(L80)
Input Voltage	220-240V AC
Input Voltage Power Factor	220-240V AC > 0.5
Power Factor	> 0.5
Power Factor Electrical Classification	> 0.5 Class I
Power Factor Electrical Classification Surge Protection	> 0.5 Class I
Power Factor Electrical Classification Surge Protection OTHERS	> 0.5 Class I Overload / Short Circuit

0.8 kg

Ø114 x 163 mm

Weight

Dimensions