



# PURO<sup>SLIM</sup>

## Ultra Slim Oyster lights



**TRITONE**  
Colour  
Selectable



**LOW**  
Profile



**Flicker**  
Free



**IP54**  
Ingress  
Protection  
Rating



**110°**  
Beam  
Angle



**85,000hr**  
Projected  
Lifespan



**5yr**  
Warranty

### Minimalist design, maximum impact.

The **PURO SLIM** is a sleek, IP54-rated LED ceiling light designed for optimal performance in general lighting applications. Its slim 26mm profile and even light distribution create a modern, minimalist aesthetic. With adjustable colour temperature options, three size variations and available in black and white finishes, the **PURO SLIM** adapts seamlessly to diverse residential settings.

### Features

- Tritone colour selectable
- Low profile design
- IP54 rating
- Flicker-free driver
- Dimmable driver
- Choice of sizes to choose from
- Class II

### Benefits

- Provides the choice of light hues from a single luminaire
- Suitable for very shallow ceiling spaces
- Suitable for wet or damp areas
- Increase productivity and lowers eye strain
- Adjustable brightness to improve comfort
- Adaptable to suit various requirements
- Reduced Risk of Electric Shock, Double insulation significantly reduces the risk of electric shock, making it a safer choice, especially in damp or wet environments.

**Product Overview**

POWER	LUMENS	EFFICACY	CCT	WEIGHT	SAP CODE	PRODUCT CODE
13 W	1196 / 1290 / 1271 lm	92 / 99 / 98 lm/W		0.47 kg	2002532	PUROSL13W-250R
					2002533	PUROSL13W-250RBK
17 W	1490 / 1625 / 1603 lm	88 / 96 / 94 lm/W	3000 / 4000 / 5700 K	0.60 kg	2002534	PUROSL17W-300R
					2002535	PUROSL17W-300RBK
24 W	2363 / 2609 / 2528 lm	98 / 109 / 105 lm/W		1 kg	2002536	PUROSL24W-400R
					2002537	PUROSL24W-400RBK

SPECIFICATIONS				APPLICATIONS	
Body Material:	Polypropylene	Driver:	Integral	Bedrooms	Hotel Common Areas
Diffuser Material:	PMMA (Acrylic)	Connect Type:	PA10 Terminals	Lounge Room	Hotel Rooms
Body Colour:	White Black	Electrical Classification:	Class II	Dining Area	Storage Rooms
IP Rating:	IP54	Projected Lifespan:	>85,000hrs @ Ta 45°C (L80)	Laundry	Temporary Installations
Flicker-free	Yes	Operating Ambient Temp.	-20 to 45°C	Hallways	
Beam Angle:	110°	Power Factor:	> 0.9	Staircase	
CRI:	> 80	Surge Protection:	Overload / Short Circuit	Walk-in Ward- robes	
Mounting Type:	Surface Mount	Smart:	KASTA Compatible	Garage	
Dimming:	Phase-Cut Dimmable (Trailing Edge, 1-100%)				
				Education Facilities	

Oysters

**DIMENSIONS**

