

PURO G4

PURO18W-350R-MS
SAP CODE: 2002375


The Puro G4 LED oyster light is designed to provide smooth light distribution and tritone colour capabilities. Available in different sizes and the option of combining a sensor and/or emergency option, the PURO G4 is a perfect all-round oyster light.

APPLICATIONS

Bedrooms, Lounge Room, Dining Area, Laundry, Hallways, Staircase, Walk-in Wardrobes, Garage, Education Facilities, Hotel Common Areas, Hotel Rooms, Storage Rooms, Temporary Installations



PHOTOMETRIC DIAGRAM



Unit: cd

— C0/180 120.0deg
— C90/270 120.4deg

Photometric diagram shown is for 4000K output.

KEY INFORMATION

Power	10 W 13 W 18 W
Lumen Output	850 / 927 / 900 lm 13W: 1120 / 1236 / 1200 lm 1700 / 1854 / 1800 lm
Mounting Type	Surface Mount
Dimming Type	Non-Dimmable
Body Colour	White
IP Rating	IP54
IK Rating	IK04
Operating Ambient Temp.	-20 to 45°C
Connection Type	PA14 Terminals
Driver	Integral
Warranty	5 yrs

PHOTOMETRIC

Efficacy	89 / 98 / 90 lm/W 90 / 99 / 96 lm/W 97 / 106 / 103 lm/W
CCT	3000 / 4000 / 5700 K
CRI	> 80
SDCM	< 5
UGR	N/A
Beam Angle	120°
Flicker-Free	No
Projected Lifespan	>50,000hrs @ Ta 25°C (L80)

ELECTRICAL

Input Voltage	220-240Vac, 50/60Hz
Power Factor	> 0.9
Electrical Classification	Class I
Surge Protection	Overload / Short Circuit

OTHERS

Body Material	Steel
Diffuser Material	PMMA
Rebate Scheme Approvals	N/A
Weight	0.61 kg
Dimensions	Ø350 x 70 mm