

PURO SLIM

PUROSL17W-300RBK SAP CODE: 2002535


Minimalist design, maximum impact

The PURO SLIM is a sleek, IP54-rated LED ceiling light designed for optimal performance in general lighting applications. Its slim 26mm profile and even light distribution create a modern, minimalist aesthetic. With adjustable colour temperature, three size variations and available in black and white finishes, the PURO SLIM adapts seamlessly to diverse residential settings.


APPLICATIONS

Bedrooms, Lounge Room, Dining Area, Laundry, Hallways, Staircase, Walk-in Wardrobes, Garage, Education Facilities, Hotel Common Areas, Hotel Rooms, Storage Rooms, Temporary Installations

DIMENSION DIAGRAMS







Unit: cd -- C0/180,113.1 -- C90/270,112.7

Photometric diagram shown is for 4000 K output.

KEY INFORMATION	
Power	17 W
Lumen Output	1490 / 1625 / 1603 lm
Mounting Type	Surface Mount
Dimming Type	Phase-Cut Dimmable (Trailing Edge, 10-100%)
Body Colour	Black
IP Rating	IP54
IK Rating	Not Applicable
Operating Ambient Temp.	-20 to 45°C
Connection Type	PA10 Terminals
Driver	Integral
Warranty	5 yrs

PHOTOMETRIC Efficacy 91.16 / 102.88 / 98.02 lm/W CCT 3000 / 4000 / 5700 K CRI > 80 SDCM < 5 UGR Not Applicable Beam Angle 110° Flicker-Free Yes		
CCT 3000 / 4000 / 5700 K CRI > 80 SDCM < 5 UGR Not Applicable Beam Angle 110° Flicker-Free Yes	PHOTOMETRIC	
CRI > 80 SDCM < 5 UGR Not Applicable Beam Angle 110° Flicker-Free Yes	Efficacy	91.16 / 102.88 / 98.02 lm/W
SDCM < 5 UGR Not Applicable Beam Angle 110° Flicker-Free Yes	CCT	3000 / 4000 / 5700 K
UGR Not Applicable Beam Angle 110° Flicker-Free Yes	CRI	> 80
Beam Angle 110° Flicker-Free Yes	SDCM	< 5
Flicker-Free Yes	UGR	Not Applicable
	Beam Angle	110°
Decided 11(5-2-2-2)	Flicker-Free	Yes
Projected Lirespan >85,000nrs @ 1a 45°C (L80)	Projected Lifespan	>85,000hrs @ Ta 45°C (L80)

ELECTRICAL	
Input Voltage	220-240Vac, 50/60Hz
Power Factor	> 0.9
Electrical Classification	Class II
Surge Protection	Overload / Short Circuit

- · J · · · · · · · ·	
OTHERS	
Body Material	Polypropylene
Diffuser Material	PMMA
Rebate Scheme Approvals	
Weight	0.6 kg
Dimensions	Ø 294 x 26 mm