

PURO SLIM

PUROSL17W-300R SAP CODE: 2002534


Minimalist design, maximum impact

The PURO SLIM is a sleek, IP54rated LED ceiling light designed for optimal performance in general lighting applications. Its slim 26mm profile and even light distribution create a modern, minimalist aesthetic. With adjustable colour temperature options, three size variations and available in black and white finishes, the PURO SLIM adapts seamlessly to diverse residential

APPLICATIONS

Bedrooms, Lounge Room, Dining Area, Laundry, Hallways, Staircase, Walk-in Wardrobes, Garage, Education Facilities, Hotel Common Areas, Hotel Rooms, Storage Rooms, Temporary Installations

DIMENSION DIAGRAMS





Photometric diagram shown is for 4000 K output.

| KEY INFORMATION | |
|----------------------------|---|
| Power | 17 W |
| Lumen Output | 1490 / 1625 / 1603 lm |
| Mounting Type | Surface Mount |
| Dimming Type | Phase-Cut Dimmable (Trailing Edge, 10- 100%) |
| Body Colour | White |
| IP Rating | IP54 |
| IK Rating | Not Applicable |
| Operating Ambient Temp. | -20 to 45°C |
| Connection Type | PA10 Terminals |
| Driver | Integral |
| Warranty | 5 yrs |
| PHOTOMETRIC | |
| Efficacy | 91.16 / 102.88 / 98.02 lm/W |
| CCT | 3000 / 4000 / 5700 K |
| CRI | > 80 |
| SDCM | < 5 |
| UGR | Not Applicable |
| Beam Angle | 110° |
| Flicker-Free | Yes |
| Projected Lifespan | >85,000hrs @ Ta 45°C (L80) |
| ELECTRICAL | |
| Input Voltage | 220-240Vac, 50/60Hz |
| Power Factor | > 0.9 |
| Electrical Classification | Class II |
| Surge Protection | Overload / Short Circuit |
| OTHERS | |
| Body Material | Polypropylene |
| Diffuser Material | PMMA |
| Rebate Scheme Approvals | |
| Weight | 0.6 kg |
| Dimensions | Ø 294 x 26 mm |

D haneco.com.au

PHOTOMETRIC DIAGRAM

120

240

360

480

60

30

60

30