

# PURO SLIM

**PUROSL24W-400R**  
SAP CODE: 2002536


## Minimalist design, maximum impact

The PURO SLIM is a sleek, IP54-rated LED ceiling light designed for optimal performance in general lighting applications. Its slim 26mm profile and even light distribution create a modern, minimalist aesthetic. With adjustable colour temperature, three size variations and available in black and white finishes, the PURO SLIM adapts seamlessly to diverse residential settings.


### APPLICATIONS

Bedrooms, Lounge Room, Dining Area, Laundry, Hallways, Staircase, Walk-in Wardrobes, Garage, Education Facilities, Hotel Common Areas, Hotel Rooms, Storage Rooms, Temporary Installations

### DIMENSION DIAGRAMS



### PHOTOMETRIC DIAGRAM



Unit: cd  
 - C0/180,113.2  
 - C90/270,112.7

Photometric diagram shown is for 4000 K output.

### KEY INFORMATION

Power	24 W
Lumen Output	2363 / 2607 / 2528 lm
Mounting Type	Surface Mount
Dimming Type	Phase-Cut Dimmable (Trailing Edge, 10-100%)
Body Colour	White
IP Rating	IP54
IK Rating	Not Applicable
Operating Ambient Temp.	-20 to 45°C
Connection Type	PA10 Terminals
Driver	Integral
Warranty	5 yrs

### PHOTOMETRIC

Efficacy	101.25 / 115.92 / 108.38 lm/W
CCT	3000 / 4000 / 5700 K
CRI	> 80
SDCM	< 5
UGR	Not Applicable
Beam Angle	110°
Flicker-Free	Yes
Projected Lifespan	>85,000hrs @ Ta 45°C (L80)

### ELECTRICAL

Input Voltage	220-240Vac, 50/60Hz
Power Factor	> 0.9
Electrical Classification	Class II
Surge Protection	Overload / Short Circuit

### OTHERS

Body Material	Polypropylene
Diffuser Material	PMMA
Rebate Scheme Approvals	
Weight	1 kg
Dimensions	Ø 400 x 26 mm