



SENTRY

SENTRY40W12-TRI

SAP CODE: 2002586

Vandal proof and secure.

SENTRY is a sturdy and vandal proof security fitting. It features a robust polycarbonate body and diffuser, designed to withstand the toughest environments.

SENTRY is ideal for public areas, schools and community centres.


APPLICATIONS

Side of Building, Manufacturing Facilities, Public Facilities, Indoor Recreation, Area Lighting

DIMENSION DIAGRAMS



PHOTOMETRIC DIAGRAM



Unit: cd

- C0/180 107.0deg
- C30/210 130.2deg
- C60/240 160.4deg
- C90/270 172.2deg

KEY INFORMATION

Power	20/40 W
Lumen Output	22 W: 2420 / 2860 / 2640 lm 40 W: 4400 / 5200 / 4800 lm
Mounting Type	Surface Mount
Dimming Type	Non-Dimmable
Fascia Colour	White
IP Rating	IP65
IK Rating	IK10
Operating Ambient Temp.	-15 to 45°C
Connection Type	PA14 Terminals
Driver	Integral
Warranty	3 yrs

PHOTOMETRIC

Efficacy	110/130/120lm/W
CCT	3000 / 4000 / 5000 K
CRI	> 80
SDCM	< 6
UGR	> 25
Beam Angle	120°
Flicker-Free	Yes
Projected Lifespan	54,000hrs @ 25°C (L70)

ELECTRICAL

Input Voltage	220-240Vac, 50/60Hz
Power Factor	> 0.9
Electrical Classification	Class I
Surge Protection	Overload / Short Circuit

OTHERS

Body Material	Polycarbonate
Diffuser Material	Polycarbonate (Opal)
Cable Entry	Rear
Rebate Scheme Approvals	
HACCP Approval	No
Weight	2535g
Dimensions	1285 x 96 x 115mm