



SKYLUX G4

Highbays

12-Highbays-in-1



The all new Skylux G4 continues Haneco's tradition of providing the leading edge in highbay technology and is a state-of-the-art highbay solution.

12-Highbays-in-1, the Skylux G4 is 4 Power Switchable and Tritone Selectable. Offering precision optics for improved performance and a tough aluminium housing with optimised heat dissipation, to ensure prolonged LED life.

The G4 has a wide range of accessories including programmable plug and play smart sensor, prismatic diffusers, Dali converters and an EM Kit.

Features

- Tritone and power switchable
- Optional plug in microwave motion sensor
- High lumen efficacy up to 175lm/W
- Flicker-free driver
- Emergency kit available
- Optional DALI converter available
- Tough diecast aluminium housing
- Various accessories available

Benefits

- Reduced SKUs and inventory levels
- Retrofittable smarts for additional power conservation
- Enhanced energy savings
- Increased health and productivity
- Provides safety in case of power outages
- Easy system integration
- Improved heat dissipation
- Extended application options



SKYLUX G4

Product Overview

POWER	LUMENS	EFFICACY	CCT	DIMENSIONS	WEIGHT	SAP CODE	PRODUCT CODE
100W	17658 lm	166 lm/W	3000K	Ø340 x 183mm	3.00kg	2002270	SKYLUX200W-G4
	17915 lm	175 lm/W	4000K				
	17798 lm	171 lm/W	5000K				
150W	24502 lm	160 lm/W	3000K				
	25322 lm	172 lm/W	4000K				
	25002 lm	165 lm/W	5000K				
170W	26860 lm	157 lm/W	3000K				
	27751 lm	168 lm/W	4000K				
	27651 lm	163 lm/W	5000K				
200W	30515 lm	152 lm/W	3000K				
	31298 lm	164 lm/W	4000K				
	31770 lm	162 lm/W	5000K				

SPECIFICATIONS


Body Material:	Aluminium
Diffuser Material:	Polycarbonate (Clear)
Body colour:	Black
IP Rating:	IP65
IK Rating:	IK08
Beam Angle:	120°
CRI:	>80
SDCM:	<5
Driver:	Integral
Power Lead:	1.5m Rubber Flex & Plug
Input:	100-277V, 50/60Hz
Electrical Classification:	Class 1

Power Factor:	>0.9
Protection:	Overload / Short Circuit
Lifespan:	>50,000hrs @Ta25°C (L70)
Operating Ambient Temperature:	-30 to 50°C
Smart:	KASTA Compatible
Dimming:	0-10V Dimmable

APPLICATIONS

Warehouses
Factories
Sheds
Industrial
Large Commercial Spaces

DIMENSIONS



FIND OUT MORE:



ACCESSORIES

Microwave Motion Sensor HIGHBAY-MS
(SAP 2002281)
• Quick connect
• 12m range with corridor function



Sensor Remote Controller HIGHBAY-REMOTE
(SAP 2002282)
• Required to reprogram sensor



Surface Mount Bracket SKYLUXG4-BRKT
(SAP 2002276)



Prismatic Reflector 200W: SKYLUX200G4-PR
(SAP 2002278)



DALI Converter HBAY-DALI-CONV
(SAP 2002095)

- IP65 rated
- Converts product to be DALI dimmable



Emergency Kit SKYLUXG4-EMKIT
(SAP 2002275)