



SKYLUX SLIM NEW

Highbays

4POWER
Switchable Modes

DIM
0-10V Dimming

IP65
Ingress Protection Rating

IK08
Impact Rating

50,000hr
Expected Lifetime

5yr
Warranty

Compact, yet powerful.

SKYLUX SLIM is the latest addition to Haneco Lighting Australia's market-leading range of highbay lighting. Using the latest LED technology, superior lumen efficacy and sleek diecast aluminium housing, SKYLUX SLIM offers everything you need for highbay lighting applications, whilst reducing your inventory costs.

Features

- Power switchable
- Optional plug in microwave motion sensor
- Optional DALI convertor available
- Sleek diecast aluminium housing
- Lumen efficacy up to 171lm/W
- Wide range of accessories

Benefits

- Reduced SKUs and inventory levels
- Enhanced energy savings
- Easy system integration
- Improved aesthetics and thermals
- Advanced energy savings
- Extended application options



SKYLUX^{SLIM}

Product Overview

POWER	LUMENS	EFFICACY	CCT	DIMENSIONS	WEIGHT	SAP CODE	PRODUCT CODE
60W	9850 lm	169 lm/W	5000K	Ø265 x 134mm	1.80kg	2002271	SKYLUX120W-SL
70W	11290 lm	166 lm/W					
90W	14369 lm	165 lm/W					
120W	18926 lm	161 lm/W					
100W	16649 lm	171 lm/W	5000K	Ø300 x 134mm	2.20kg	2002272	SKYLUX200W-SL
150W	23608 lm	165 lm/W					
170W	26567 lm	163 lm/W					
200W	31539 lm	162 lm/W					

SPECIFICATIONS

Body Material:	Aluminium
Diffuser Material:	Polycarbonate (Clear)
Body colour:	Black
IP Rating:	IP65
IK Rating:	IK08
Beam Angle:	120°
CRI:	>80
SDCM:	<5
Driver:	Integral
Power Lead:	1.5m Rubber Flex & Plug
Input:	100-277V, 50/60Hz
Electrical Classification:	Class 1

Power Factor:	>0.9
Protection:	Overload / Short Circuit
Lifespan:	>50,000hrs @Ta25°C (L70)
Operating Ambient Temperature:	-30 to 50°C
Smart:	KASTA Compatible
Dimming:	0-10V Dimmable

APPLICATIONS

Warehouses
Factories
Sheds
Industrial
Large Commercial Spaces

ACCESSORIES

Microwave Motion Sensor HIGHBAY-MS
(SAP 2002281)
• Quick connect
• 12m range with corridor function



Sensor Remote Controller HIGHBAY-REMOTE
(SAP 2002282)
• Required to reprogram sensor



Surface Mount Bracket SKYLUXG4-BRKT
(SAP 2002276)



Prismatic Reflector 120W: SKYLUX120G4-PR
(SAP 2002277)
200W: SKYLUX200G4-PR
(SAP 2002278)





DALI Converter HBAY-DALI-CONV
(SAP 2002095)



- IP65 rated
- Converts product to be DALI dimmable



DIMENSIONS



SKYLUX120W-SL



SKYLUX200W-SL

FIND OUT MORE:

