

# SKYLUX EVO

**SKYLUX200W-EV**  
SAP CODE: 2002420



## Sleek and powerful.

SKYLUX EVO is a power switchable LED highbay, suitable for many commercial and industrial applications with high ceilings, and a need for high visibility and effective productivity.

### APPLICATIONS

Warehouse, Storage Facilities,  
Manufacturing Facilities, Cool Rooms,  
General Industrial

### DIMENSION DIAGRAMS



### KEY INFORMATION

Power	100 W 150 W 170 W 200 W
Lumen Output	18,829 lm 25,677 lm 28,317 lm 31,479 lm
Mounting Type	Suspended
Dimming Type	0-10V Dimmable
Body Colour	Black
IP Rating	IP65
IK Rating	IK08
Operating Ambient Temp.	-30 to 50°C
Connection Type	1.5m Rubber Flex & Plug
Driver	Integral
Warranty	5 yrs

### PHOTOMETRIC

Efficacy	100W: 182 lm/W 150W: 173 lm/W 170W: 166 lm/W 200W: 160 lm/W
CCT	5000 K
CRI	> 70
SDCM	< 5
UGR	> 25
Beam Angle	120°
Flicker-Free	Yes
Projected Lifespan	>54,000hrs @ Ta 25°C (L70)

### ELECTRICAL

Input Voltage	190-268V, 50/60Hz
Power Factor	> 0.9
Electrical Classification	Class I
Flicker-free	Yes
Surge Protection	Overload / Short Circuit

### OTHERS

Body Material	Die Cast Aluminium
Diffuser Material	Polycarbonate (Clear)
HACCP Approval	No
Rebate Scheme Approvals	
Weight	1.8 kg
Dimensions	Ø290 x 147 mm