



SKYLUX^{X3}

SKYLUX200W-X3

SAP CODE: 2002607



Triple the Flexibility. One Versatile Highbay.

SKYLUX^{X3} LED Highbay is a 27-in-1 LED Highbay solution, featuring an innovative adjustable beam angle system (3 x beam angles), 3 x power settings and 3 x selectable colour temperatures; all-in-one unit.

APPLICATIONS

Warehouse, Storage Facilities,
Manufacturing Facilities, Cool Rooms,
General Industrial


DIMENSION DIAGRAMS



*Based on designed LED lifetime



PHOTOMETRIC DIAGRAM



Unit: cd

— C0/180 105.7deg

— C90/270 105.3deg

KEY INFORMATION

Power	100 W 150 W 200 W
Lumen Output	15,862 / 17,038 / 17,243 lm (120°) 22,517 / 24,813 / 24,883 lm (120°) 34,769 / 35,507 / 35,840 lm (120°)
Mounting Type	Suspended
Dimming Type	0-10V Dimmable
Body Colour	Black
IP Rating	IP65
IK Rating	IK08
Operating Ambient Temp.	-30 to 50°C
Connection Type	1.5m Rubber Flex & Plug
Driver	Integral
Warranty	5 yrs

PHOTOMETRIC

Efficacy	100 W: 161 / 177 / 176 lm/W (120°) 150 W: 153 / 173 / 170 lm/W (120°) 200 W: 175 / 185 / 183 lm/W (120°)
CCT	3000 / 4000 / 5000 K
CRI	> 80
SDCM	< 7
UGR	> 25
Beam Angle	70° / 90° / 120°
Flicker-Free	Yes
Projected Lifespan	>102,000hrs @ Ta 25°C (L80)*

ELECTRICAL

Input Voltage	220-240 Vac, 50/60 Hz
Power Factor	> 0.9
Electrical Classification	Class I
Flicker-free	Yes
Surge Protection	Overload / Short Circuit

OTHERS

Body Material	Die Cast Aluminium
Diffuser Material	Polycarbonate (Clear)
HACCP Approval	No
Rebate Scheme Approvals	No
Weight	2.15 kg
Dimensions	Ø320 x 170 mm