

YOUR
SMART
ENERGY

BATTERY

SMILE-BAT-5P

RESIDENTIAL SERIES

CAPACITY

5.04 kWh Module





Modular

Plug & Play

Safe

Long Lifespan



BATTERY SMILE-BAT-5P



Model	SMILE-BAT-5P
Physical	
Battery Type	LFP (LiFePO ₄)
Weight	48 kg
Dimensions (W x D x H)	640 x 250 x 345 mm
IP Protection	IP65 (Outdoor)
Warranty	10 Years Battery Performance Warranty
Electrical	
Energy Capacity	5.04 kWh
Usable Capacity	4.788 kWh
Depth of Discharge (DoD)	95%*
Nominal Voltage	48 V
Operating Voltage Range	45 ~ 54 V
Cycle Life	6000**
Operation	
Max. Charging Current	60 A
Max. Discharging Current	60 A
Operating Temperature Range	-10 °C ~ 50 °C***
Relative Humidity	0 ~ 95% (No Condensation)
BMS	
Modules Connection	1 ~ 6 SMILE-BAT-5P in parallel
Energy Capacity	5.0 / 10.1 / 15.1 / 20.2 / 25.2 / 30.2 kWh
Usable Capacity	4.8 / 9.6 / 14.4 / 19.2 / 23.9 / 28.7 kWh
Monitoring Parameters	System voltage, current, cell voltage, cell temperature, PCBA temperature
Communication	CAN and RS-485 compatible
Certification	
Transportation	UN 38.3
Safety	IEC 62619 (Cell), IEC 62619 (Pack)



- ≈ +86 513 8060 6891
 ≈ info@alpha-ess.com
 € www.alphaess.com
 型 Jiuhua Road 888, Nantong High-Tech Industrial Development Zone, Nantong, Jiangsu Province, China

- a +39 339 462 4288 a info@alpha-ess.it b www.alphaess.com b Via Don Minzoni, 17,Calenzano a Firenze 50041 Italy

- ***** +49 610 3459 1601
- ≈ europe@alpha-ess.de ℰ www.alphaess.de Թ Paul-Ehrlich-Straße la,Langen, Hessen D-63225 Germany

- a +44 0330 043 2610 info@alpha-ess.com Drake house, Long street, Dursley, gl11 4hh UK

- # +61 02 9000 7676

 Australia@alpha-ess.com

 www.alphaess.com

 8/15-21 Glibbes Street, Chatswood,
 NSW 2067 Australia

- **a** +1 408 368 7828

- a +65 6513 1125 / +65 6513 1126
 Singapore@alpha-ess.com
 Corporation Road #01-06A
 Corporation Place 618494
 Singapore

^{*} Test condition: Max. 0.5C charge/discharge at 25±2 °C.

** Under specific test conditions.

*** Max. charge/discharge current derating may occur with changes in temperature and SoC.